

# Safety Data Sheet

Date of issue: 1/22/2016

Version: 1.0

FOR INDUSTRIAL USE ONLY

MARINE CLEAR

# Section 1. Product and company identification

Product Name:	Gel Coat ISO/NPG Series - MARINE CLEAR
	ArmorFlex
SDS Number:	963XK161
Product Use:	Industrial
Manufacturer, Importer, Supplier	Polynt Composites USA, Inc. 99 East Cottage Avenue Carpentersville IL 60110
	E-Mail: MSDS@pccrusa.com
Telephone	For Emergency Transportation Information CHEMTREC US Domestic (800) 424-9300 CHEMTREC International (703) 527-3887

For additional health and safety or regulatory information, call 1 847-836-3627.

# Section 2. Hazard(s) identification

**EMERGENCY OVERVIEW:** May cause sensitization by inhalation and skin contact. Risk of serious damage to the lungs (by aspiration).

#### **GHS Classification**

Acute Tox. 4 Inhalation, Carc. 2, Eye Irrit. 2, Flam. Liq. 3, Repr. 2, Skin Irrit. 2, Skin Sens. 1, STOT RE 1

Symbol(s) of Product



Signal Word Danger

## GHS HAZARD STATEMENTS

Flammable Liquid, category 3	H226	Flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.

. . . . .

Date Printed: 1/11/2016

Carcinogenicity, category 2	H351	Suspected of causing cancer. Classified as Category 2 based on limited evidence on human and/or animal studies. Mixtures with concentrations of suspected carcinogens ingredients at concentration present between 0.1% and 1.0% labelling the SDS will be optional depending on authorities. If Category 2 carcinogenic present at a concentration of 1% or above labelling the SDS will be expected. Routes of exposure are dependent on ingredient form.	
Reproductive Toxicity, category 2	H361	Suspected of damaging fertility or the unborn child. Classifed Category 2 suspected human reproductive toxicant irreversible effects such as structural malfunctions, embryo/foetal lethality, post natal functional deficiencies.	
STOT, repeated exposure, category 1	H372	Causes damage to organs <or affected,="" all="" if="" known="" organs="" state=""> through prolonged or repeated exposure <state cause="" conclusively="" exposure="" hazard="" if="" is="" it="" no="" of="" other="" proven="" route="" routes="" that="" the="">.</state></or>	
GHS LABEL PRECAUTIONARY STATE	MENTS		
P201		cial instructions before use.	
P210		from heat, hot surfaces, sparks, open flames and other ignition sources. No	
P233	Keep conta	iner tightly closed.	
P260	Do not brea	the dust/fume/gas/mist/vapours/spray.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.		
P281	Use personal protective equipment as required.		
P302+P352	IF ON SKIN	I: Wash with plenty of soap and water.	
P305+P351+P338		: Rinse cautiously with water for several minutes. Remove contact lenses, if leasy to do. Continue rinsing.	
P308+P313	IF exposed	or concerned: Get medical advice/attention.	
P312	Call a POIS	ON CENTER or doctor/physician if you feel unwell.	
P333+P313	If skin irritat	ion or rash occurs: Get medical advice/attention.	
P337+P313	If eye irritation persists: Get medical advice/attention.		
P362	Take off contaminated clothing.		
P403+P235	Store in a well-ventilated place. Keep cool.		
P501	Dispose of regulations	contents/container to in accordance with local/regional/national/international	
GHS SDS PRECAUTIONARY STATEM	ENTS		
P240		nd container and receiving equipment.	
P241	Use explos	ion-proof electrical/ventilating/lighting// equipment.	
P242	Use only non-sparking tools.		
P243	Take precautionary measures against static discharge.		
P270	Do no eat, drink or smoke when using this product.		
P363	Wash conta	aminated clothing before reuse.	

# Section 3. Composition/Information on ingredients

<u>Chemical Name</u> STYRENE MONOMER	<u>CAS-No.</u> 100-42-5	<u>Wt. %</u> 36.87	<u>GHS Symbols</u> GHS02-GHS07- GHS08	GHS Statements H226-302-315-319-332-351-361 -372
METHYL METHACRYLATE LIGHT AROMATIC NAPHTHA ETHYLBENZENE	80-62-6 64742-95-6 100-41-4	5.0 - 10 0.1-1.0 0.1-1.0	GHS02-GHS07 GHS07-GHS08 GHS02-GHS07- GHS08	-372 H225-315-317-332-335 H304-332-351 H225-304-332-373

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

## Section 4. First-aid measures



**FIRST AID - EYE CONTACT:** If symptoms persist, call a physician. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

**FIRST AID - INGESTION:** Aspiration hazard if swallowed - can enter lungs and cause damage. If ingested, consult a physician. Do NOT induce vomiting.

FIRST AID - INHALATION: Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit

may result in adverse health effect, such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Give oxygen or artificial respiration if needed. Move to fresh air in case of accidental inhalation of vapours. Remove person to fresh air. If signs/symptoms continue, get medical attention.

**FIRST AID - SKIN CONTACT:** Wash contaminated clothing before reuse. Wash skin with soap and water for several minutes. Get medical attention if irritation develops. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Prolonged skin contact may defat the skin and produce dermatitis.

## Section 5. Fire-fighting measures

#### Extinguishing Media:

SuitableCarbon Dioxide, Dry Chemical, Foam, Water FogNot suitableWater Jet

**SPECIAL FIREFIGHTING PROCEDURES:** Use full protective clothing. Use a properly-fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Water spray. Dry powder. Carbon dioxide (CO2). Do not use a solid water stream as it may scatter and spread fire. Cool containers / tanks with water spray. Vapors may be ignited by heat, pilot lights, other flames and ignition sources. Self-accelerating decomposition may occur if the specific control temperature is not maintained. Vapors may accumulate in confined areas (basement, tanks, hopper/tank cars, etc.).

#### UNUSUAL FIRE AND EXPLOSION HAZARDS: No Information

## Section 6. Accidental release measures

**ENVIRONMENTAL MEASURES:** Prevent entry into waterways, sewers, basements or confined areas. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike to prevent entering any sewer or waterway. Transfer liquid to a holding container. Avoid breathing vapors or mists. Use non-sparking tools and equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. Do not flush into surface water or sanitary sewer system. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

#### PRECAUTIONARY MEASURES: No Information

## Section 7. Handling and storage



HANDLING: Avoid contact with skin, eyes and clothing. Ground/bond container and equipment. Wear personal protective equipment. Use only in well-ventilated areas. Keep away from heat and sources of ignition. Do not breathe vapors, mist or gas.

**STORAGE:** Store contents under 100F (37.8C). Store drums with bung in the upright position. Electrical equipment must be grounded; suitable for the classification of the area where it is installed and conform to the National Electric Code (see NFPA 70). Keep container closed when not in use. Store and dispose according to national, state and local regulations.

**HYGIENIC PRACTICES:** When using, do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing. General industrial hygiene practice. Wash hands before eating, drinking, or smoking.

**WORK PRACTICES:** Put on appropriate personal protective equipment. Wash hands after handling chemicals and before eating, drinking, or smoking. Read and understand entire SDS before handling chemical.

**SPECIAL HANDLING PROCEDURES:** Put on appropriate personal protective equipment. Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored, and processed. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use.

## Section 8. Exposure controls/personal protection

#### Ingredients with Occupational Exposure Limits

Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	<u>OSHA PEL-TWA</u>	OSHA CEILING
STYRENE MONOMER	20 ppm	40 ppm	100 ppm	200 ppm
METHYL METHACRYLATE	50 ppm	100 ppm	100 ppm	N.E.
LIGHT AROMATIC NAPHTHA	N.E.	N.E.	N.E.	N.E.
ETHYLBENZENE	20 ppm	N.E.	100 ppm	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

#### **Personal Protection**



**RESPIRATORY PROTECTION:** When concentrations exceed the exposure limits specified, use of a NIOSH-approved dust, mist and fume respirator is recommended. Where the protection factor of the respirator may be exceeded, use of a full facepiece, supplied air, or Self Contained Breathing Apparatus (SCBA) may be necessary. Use a properly-fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.



**SKIN PROTECTION:** Wear suitable protective equipment. Wear chemical resistant footwear and clothing such as gloves, an apron or a whole body suit as appropriate.



**EYE PROTECTION:** Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses with side-shields. Wear chemical-resistant glasses and/or goggles and a face shield when eye and face contact is possible due to splashing or spraying of material.



**OTHER PROTECTIVE EQUIPMENT:** Use good hygiene practices. Wash face and hands before eating, drinking, and smoking. Eye wash and safety showers should be readily available.



**HYGIENIC PRACTICES:** When using, do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing. General industrial hygiene practice. Wash hands before eating, drinking, or smoking.

## Section 9. Physical and chemical properties

Color:	Translucent	Physical State:	Liquid
Odor:	Moderate aromatic	Odor Threshold:	Not Available
Density, g/cm3:	1.059	pH:	Not Available
Freeze Point, °C:	Not Available	Viscosity:	Not Available
Solubility in Water:	Insoluble	Partition Coefficient, n-octanol/ water:	Not Available
Decompostion Temp., °C:	Not Available	Flash Point, °C / F°	26 / 79
Boiling Range, °C:	0	Explosive Limits, vol%:	Not Available
Vapor Pressure:	Not Available	Auto-ignition Temp., °C:	Not Available

(See "Other information" Section for abbreviation legend)

## Section 10. Stability and reactivity

**STABILITY:** The product is normally supplied in a stabilized form. If the permissible storage period and/or storage temperature is noticeably exceeded, the product may polymerise with heat evolution. Stable under normal conditions.

**CONDITIONS TO AVOID:** Avoid improper addition of promotor and/or catalyst. Avoid direct contact of MEKP catalyst with accelerator. If adding accelerator like cobalt drier, mix accelerator with base material before adding catalyst. Burning may produce obnoxious and toxic fumes. Hazardous polymerization may occur. Keep product away from heat, sparks, pilot lights, static electricity, and open flame.

**INCOMPATIBILITY:** Aluminium. Free radical initiators. Bases. Copper. Strong acids. Strong acids, strong bases, strong oxidizing agents. Strong oxidizing and reducing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: None under normal use.

## Section 11. Toxicological information



#### Practical Experiences

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** Presumed to be moderately irritating to the eyes. Exposure may cause mild irritation. Symptoms may include stinging, tearing, and redness.

**EFFECT OF OVEREXPOSURE - INGESTION:** May cause severe gastrointestinal disturbance with headache, nausea, vomiting and diarrhea.

**EFFECT OF OVEREXPOSURE - INHALATION:** Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes). Prolonged, repeated or high exposures may cause central nervous system depression leading to headaches, nausea, drowsiness, dizziness, and possibly narcosis. In extreme cases, may cause loss of consciousness. Ingestion of large doses may cause headaches, dizziness, nausea, vomiting, and drowsiness. Irritating to skin.

EFFECT OF OVEREXPOSURE - SKIN CONTACT: No Information

**EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS:** Repeated or prolonged exposure may cause central nervous system damage. Prolonged skin contact may defat the skin and produce dermatitis. Prolonged or repeated exposure may cause liver and kidney effects.

**CARCINOGENICITY:** \* This product contains the following chemicals classified by the International Agency for Research on Cancer (IARC) as 1, 2A, or 2B carcinogens:

\*This product may contain a chemical which is listed in the NTP report on carcinogens.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Contact

#### **Acute Toxicity Values**

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.Name according to EEC100-42-5STYRENE MONOMER80-62-6METHYL METHACRYLATE64742-95-6LIGHT AROMATIC NAPHTHA100-41-4ETHYLBENZENE

<u>Oral LD50</u> 1000 mg/kg Rat 7900 mg/kg Rat N.I. 3500 mg/kg Rat

Dermal LD50	Vapor LC50
N.I.	11.7 mg/L Rat
N.I.	N.I.
>2000 mg/kg Rabbit	N.I.
15400 mg/kg Rabbit	17.2 mg/L Rat

N.I. - No Information

## Section 12. Ecological information

**ECOLOGICAL INFORMATION:** Ecological evaluation of this material has not been performed; however, do not allow the product to be released to the environment without governmental approval/permits. Discharge into the environment must be avoided.

#### Section 13. Disposal considerations



**DISPOSAL METHOD:** The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should always comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains, and sewers.

#### Section 14. Transport information

SPECIAL TRANSPORT PRECAUTIONS: No Information

#### International transport regulations

Regulatory	UN/NA Number	Proper Shipping Name	Classes/ *PG	Reportable Quantity (RQ)
CFR	UN1866	RESIN SOLUTION	Class 3 PGIII	
IMO/IMDG	UN1866	RESIN SOLUTION	Class 3 PGIII	
ΙΑΤΑ	UN1866	RESIN SOLUTION	Class 3 PGIII	

## Section 15. Regulatory information

## U.S. Federal Regulations:

#### **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Chemical Name	CAS-No.
STYRENE MONOMER	100-42-5
METHYL METHACRYLATE	80-62-6
ETHYLBENZENE	100-41-4

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

STYRENE MONOMER100-42-5METHYL METHACRYLATE80-62-6FTHYL BENZENE100-41-4	<u>Chemical Name</u>	<u>CAS-No.</u>
	METHYL METHACRYLATE	80-62-6

#### TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

# U.S. State Regulations:

## NEW JERSEY RIGHT-TO-KNOW:

The following hazardous materials are listed.

Chemical Name	CAS-No.
STYRENE MONOMER	100-42-5
METHYL METHACRYLATE	80-62-6
ETHYLBENZENE	100-41-4
MINERAL SPIRITS(PETROLEUM NAPHTHA)	64742-88-7
ISOPROPYL ALCOHOL	67-63-0
4-METHOXYPHENOL	150-76-5
MINERAL SPIRITS	8032-32-4
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2
METHYL ALCOHOL	67-56-1

#### PENNSYLVANIA RIGHT-TO-KNOW

The following hazardous ingredients are present:

<u>Chemical Name</u>	CAS-No.
STYRENE MONOMER	100-42-5
METHYL METHACRYLATE	80-62-6
ETHYLBENZENE	100-41-4
DIETHYLENE GLYCOL	111-46-6
ISOPROPYL ALCOHOL	67-63-0
4-METHOXYPHENOL	150-76-5
MINERAL SPIRITS	8032-32-4

ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2
METHYL ALCOHOL	67-56-1

# U.S. State Regulations:

The following hazardous materials are listed.

Chemical Name	CAS-No.
STYRENE MONOMER	100-42-5
METHYL METHACRYLATE	80-62-6
ETHYLBENZENE	100-41-4
ISOPROPYL ALCOHOL	67-63-0
4-METHOXYPHENOL	150-76-5
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2
METHYL ALCOHOL	67-56-1

#### **CALIFORNIA PROPOSITION 65 CARCINOGENS**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

Chemical Name	CAS-No.
ETHYLBENZENE	100-41-4

## **CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

<u>Chemical Name</u>	CAS-No.
METHYL ALCOHOL	67-56-1

## International Regulations

### **CANADIAN WHMIS:**

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class:	B2,D2A	
Chemical Inventories	Australia inventory (AICS)	Not Determined
	Canada inventory (DSL)	Not Determined
	Japan Inventory (ENCSC)	Not Determined
	China Inventory (IECSC)	Not Determined
	Korea Inventory (KECI)	Not Determined
	New Zealand (NZIoC)	Not Determined
	Philippines (PICCS)	Not Determined
	United States Inventory (TSCA 8b)	All components are listed or exempted

# Section 16. Other information, including date of preparation of the last revision

Revision Date:	11/23/2015 Supercedes Date: New SD							
Reason for revision:	No Informati	No Information						
Datasheet produced by:	Regulatory [	Department						
HMIS Ratings:								

Health:	2*	Flammability:	3	Reactivity:	2	Personal Protection:	N.I.	Chronic Rating:	*	
	<b>.</b>	<b>^</b>								

Volatile Organic Compounds, gr/ltr: Not Determined

### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer. Classified as Category 2 based on limited evidence on human and/or animal studies. Routes of exposure are dependent on ingredient form.
H361	Suspected of damaging fertility or the unborn child. Classifed Category 2 suspected human reproductive toxicant.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
loope for GHS E	Dictograms shown in Section 3 describing each ingredient:

Icons for GHS Pictograms shown in Section 3 describing each ingredient:



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information provided herein was believed by Polynt Composites USA, Inc. to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by Polynt Composites USA, Inc. are subject to Polynt Composites USA, Inc terms and conditions of sale. Polynt Composites USA, Inc. MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY Polynt Composites USA, Inc, except that the product shall conform to Polynt Composites USA, Inc. specifications. Nothing contained herein constitutes an offer for the sale of any product.