

Revision date: 04/27/2015

Version: 2.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **Product identifier** 1.1.

Product name : AF33 Product form : liquid Other means of identification : 3300 series

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Antifouling

#### Details of the supplier of the safety data sheet 1.3.

Sea Hawk Paints Oceania NZ New Nautical Coatings Inc. Mfg.

21-23 Timothy Place Avondale 14805 49th Street

Clearwater Florida USA 33762 Auckland New Zealand 1026

Phone +64210350506 USA Only: 1-800-528-0997 International: (727) 523-8053

#### 1.4. **Emergency telephone numbers**

Emergency number : CHEMTREC day or night inside USA & Canada

1-800-424-9300

: CHEMTREC day or night outside USA & Canada

+1-703-741-5970 : Poison Control Center

USA 1-800-222-1222 AU +61 13 11 26 NZ 0800 764 766

### **SECTION 2: Hazards identification**

### Classification of the substance or mixture

#### Classification (GHS-US)

Flam. Liq. 3 H226 Acute Tox. 4 H302 Asp. Tox. 1 H304 Aquatic Chronic 1 H410 Aquatic Acute 1 H400 Skin Sens. 1 H317 Carc. 1A H350

Contains 9.5% ingredients of unknown oral toxicity.

#### 2.2. Label elements

### **GHS-US** labeling

Signal word (GHS-US)

Hazard pictograms (GHS-US)



GHS07





Danger

Hazard statements (GHS-US) : H226 - Flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H302 - Harmful if swallowed

H317 - May cause an allergic skin reaction

H350 - May cause cancer H400 - Very toxic to aquatic life

H410- Very toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use

> P202 - Do not handle until all safety precautions have been read and understood P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical/ventilating/lighting equipment

07/28/2015 AF33 Page 1 P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge

P261 - Avoid breathing fumes or mist.

P264 - Wash face, hands and forearms thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P272 - Contaminated work clothing must not be allowed out of the workplace

P273 - Avoid release to the environment

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301+P310 - IF SWALLOWED: Immediately call a doctor.

P301+P312 - If swallowed: Call POISON CENTER or a doctor if you feel unwell

P302+P352 - If on skin: Wash with plenty of water.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water

P308+P313 - If exposed or concerned: Get medical advice/attention

P321 - Specific treatment (see first aid instructions on this label)

P330 - Rinse mouth

P331 - Do NOT induce vomiting

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention

P362+P364 - Take off contaminated clothing and wash it before reuse

P370+P378 - In case of fire: Use water to extinguish

P391 - Collect spillage

P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents/container to licenced waste handling facility.

NZEPA Approval: HSR100869

HSNO: 3.1C, 6.1D, (ALL), 6.1D (0), 6.3B, 6.4A, 6.5B, 6.7B, 6.8B, 6.8C, 6.9B, (ALL), 6.9B, (1), 6.9B, (0), 9.1A, (ALL), 9.1A, (M), 9.3B

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS-US)

No data available

# **SECTION 3: Composition/information on ingredients**

#### 3.1. Substance

Substance type:

: Multi-constituent

Name	Product identifier	%
Cupric oxide	(CAS No) 1317-38-0	1-5
Solvent naphtha(petroleum), light aromatic	(CAS No) 64742-95-6	10-30
Ethylbenzene	(CAS No) 100-41-4	0.01 - 1
Zinc oxide	(CAS No) 1314-13-2	5-10
Cuprous oxide	(CAS No) 1317-39-1	30-45
Cumene	(CAS No) 98-82-8	0.1-1
Pseudocumene	(CAS No) 95-63-6	5-10
C18-28 Long Chain Chlorinated Paraffins	(CAS No) 63449-39-8	0.1-1
Reaction product of epichlorohydrin and bisphenol A	(CAS No) 25085-99-8	0.1-1
Crystalline silica (quartz)	(CAS No) 14808-60-7	0.1-1

Full text of H-phases: see section 16

## 3.2. Mixture

Not applicable

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a

POISON CENTER or doctor/physician.

First-aid measures after skin contact : IF ON SKIN: Immediately rinse with plenty of water (for at least 15 minutes). Get immediate medical

advice/attention.

First-aid measures after eye contact : IF IN EYES: Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). Get medical advice/attention.

07/28/2015 AF33 2/10

# Safety Data Sheet

First-aid measures after ingestion IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation May cause nose and throat irritation

Symptoms/injuries after skin contact May cause skin irritation. May cause alleggic skin reaction.

Symptoms/injuries after eye contact : May cause eye irritation. Avoid contact with eyes.

Symptoms/injuries after ingestion : Harmful if swallowed. May cause abdominal pain, nausea, vomiting or drowsiness.

Chronic symptoms : Possible cancer hazard. Contains ingredients which may cause cancer based on animal data.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry powder. Alcohol-resistant foam. Water spray.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor. May produce carbon oxides under fire conditions.

Explosion hazard : Product is not explosive.

: No dangerous reactions known under normal conditions of use. Reactivity

5.3. Advice for firefighters

Firefighting instructions Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.

Do not dispose of fire-fighting water in the environment.

Protection during firefighting Do not enter fire area without proper protective equipment, including respiratory protection. Wear self-

contained breathing apparatus and protective suit (see item 8).

### **SECTION 6: Accidental release measures**

### Personal precautions, protective equipment and emergency procedures

General measures Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained clean-up crews properly

equipped with respiratory equipment and full chemical protective gear (see Section 8).

6.1.1. For non-emergency personnel

: Wear protective equipment as described in Section 8. Protective equipment

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment Wear suitable protective clothing, gloves and eye or face protection. Wear approved supplied-air

respirator, in case of emergency

#### 6.2. **Environmental precautions**

Prevent entry to sewers and public waters. Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up Exclude sources of ignition and ventilate the area. Soak up spills with inert solids, such as clay or

diatomaceous earth as soon as possible. Place in a suitable container for disposal in accordance with the

waste regulations (see Section 13). Waste from this product may be hazardous.

#### 6.4. Reference to other sections

No additional information available

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling Do not handle until all safety precautions have been read and understood. Wash hands and other exposed

areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mists. Keep away from sources of

ignition - No smoking. Use appropriate personal protection equipment (PPE).

#### 7.2. Conditions for safe storage, including any incompatibilities

Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep Storage conditions

container closed when not in use.

Storage temperature < 38 °C (100°F)

#### Specific end use(s)

No additional information available

07/28/2015 3/10 AF33

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### **Exposure**

Ethylbenzene (100-41-4)	
ACGIH TWA (ppm)	20 ppm
OSHA PEL (TWA) (mg/m³)	435 mg/m³
OSHA PEL (TWA) (ppm)	100 ppm
OSHA PEL (STEL) (mg/m³)	545 mg/m³
OSHA PEL (STEL) (ppm)	125 ppm

Zinc oxide (1314-13-2)	
ACGIH TWA (mg/m³)	2 mg/m³
ACGIH STEL (mg/m³)	10 mg/m <sup>3</sup>
Cuprous oxide (1317-38-0)	
ACGIH TWA (ppm)	No Established Limit
ACGIH STEL (ppm)	No Established Limit

Cumene (98-82-8)			
ACGIH TWA (ppm)	50 ppm		
OSHA PEL (TWA) (mg/m³)	245 mg/m³		
OSHA PEL (TWA) (ppm)	50 ppm		
Silica: Crystalline, quartz (14808-60-7)			
ACGIH TWA (mg/m³)	0.025 mg/m³ (respirable fraction)		
OSHA PEL (TWA) (mg/m³)	(10)/(%SiO2 + 2) total dust; (10)/(%SiO2 + 2) respirable fraction		
OSHA PEL (TWA) (ppm)	(250)/(%SiO2 + 5) respirable fraction		
Chlorinated paraffin waxes and hydrocarbon waxes (6344	9-39-8)		
Remark (ACGIH)	OELs not established		
Remark (OSHA)	OELs not established		

#### 8.2. **Exposure controls**

: Ensure adequate ventilation, especially in confined areas. Handle with good industrial hygiene and safety. Appropriate engineering controls Personal protective equipment : Face shield. Respiratory protection of the dependent type. Gloves. Protective goggles. Protective clothing.











Hand protection

Eye protection

Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Natural rubber ("latex"), Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or

: Eye protection, including both chemical splash goggles and face shield, must be worn when possibility

exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection Wear long sleeves. Handle with gloves

Respiratory protection An approved organic vapor respirator/supplied air or self-contained breathing apparatus must be used

when vapor concentration exceeds applicable exposure limits.

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid Appearance : liquid.

Color Dark Blue, Green, Red, Blue and Black

Odor Aromatic odour. Odor Threshold No data available : No data available pН Relative evaporation rate (butyl acetate=1) Not Measured Relative evaporation rate (ether=1) Not Measured Melting point : No data available

07/28/2015 AF33 4/10

# Safety Data Sheet

Freezing point : No data available
Boiling point : Not Measured

Flash point : 38°C (101°F)-closed cup

Self ignition temperature : Na data avilable

Decomposition temperature : No data available Flammability (solid, gas) : No data available Vapor pressure : Not Measured Relative vapor density at 20 °C : Heavier than air

Relative density : 1.86 g/ml at 25°C (77°F)

Solubility Water: None Log Pow : No data available : No data available Log Kow Viscosity, kinematic No data available Viscosity, dynamic No data available Explosive properties No data available Oxidizing properties : No data available Explosive limits : No data available

#### 9.2. Other information

No additional information available

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Upon combustion:CO and CO2 are formed.Reacts violently with strong oxidizers:increased risk of fire/explosion.reacts with some acids.

#### 10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

# 10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air.

#### 10.4. Conditions to avoid

Sparks. Heat. Open flame. Extremes of tempearture and direct sunlight.

# 10.5. Incompatible materials

Avoid contact with: Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

# **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15354 mg/kg
LC50 inhalation rat (mg/l)	17.2 mg/l/4h
ATE (oral)	3500.000 mg/kg body weight
ATE (dermal)	15354.000 mg/kg body weight
ATE (dust, mist)	1.500 mg/l/4h

<b>Cuprous oxide (1317-39-1)</b>	
LD50 oral rat	470 mg/kg Category 4
LD50 skin rabbit	2000.00 mg/kg Category 4
LD50 inhalation vapor rat	No data available
LD50 inhalation dust/mist_rat	50.00 mg/l/4h Category NA

Zinc oxide (1314-13-2)		
LD50 oral rat	5000 mg/kg Category 5	
LD50 skin rabbit	No data available	
LD50 inhalation vapor rat	No data available	

07/28/2015 **AF33** 5/10

# Safety Data Sheet

Zinc oxide (1314-13-2)			
LD50 inhalation dust/mist mouse	2.50 mg/l/4h Category 4		
Cumene (98-82-8)			
LD50 oral rat	1400 mg/kg		
LD50 dermal rabbit	12300 μg/kg		
LC50 inhalation rat (ppm)	> 3577 ppm 6 h		
Silica: Crystalline, quartz (14808-60-7)			
LD50 oral rat	500 mg/kg		
Carcinogenicity data:			
Ethylbenzene (100-41-4)			
IARC group	2B - Possibly carcinogenic to humans		
Cumene (98-82-8)			
IARC group	2B - Possibly carcinogenic to humans		
Toluene (108-88-3)			
IARC group	3 - Not classifiable		
Silica: Crystalline, quartz (14808-60-7)			
IARC group	1 - Carcinogenic to humans		
Arsenic (7440-38-2)			
IARC group	1 - Carcinogenic to humans		
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens		
Chlorinated paraffin waxes and hydrocarbon wa	,		
IARC group	2B - Possibly carcinogenic to humans		
Skin corrosion/irritation	: Not classified		
Serious eye damage/irritation	: Not Applicable, Not classified		
Respiratory or skin sensitization	: May cause an allergic skin reaction.		
Germ cell mutagenicity	: Not Applicable, Not classified		
Carcinogenicity	: May cause cancer		
Acute Toxicity(Mouth)	Harmful if swallowed.		
Acute Toxicity( skin)	Not Classified		
Reproductive toxicity	: Not Applicable, Not classified		

# **SECTION 12: Ecological information**

Specific target organ toxicity (single exposure)

Specific target organ toxicity (repeated exposure)

# 12.1. Toxicity

Aspiration hazard

Cuprous oxide (1317-39-1)	
LC50 fishes 1	0.075 mg/l (96 h;danio rerio)
EC50 daphnia 1	0.042 mg/l (48 h; Daphnia similis)
Threshold limit algae 1	0.03 mg/l (96 h; Pseudokirchneriella subcapitata)

: May be fatal if swallowed and enters airways

: Not Applicable, Not classified

: Not Applicable, Not classified

Zinc oxide (1314-13-2)	
LC50 fishes 1	1.10 mg/l (96 h; Oncorhynchus mykiss)
EC50 daphnia 1	0.098 mg/l (48 h; Daphnia magna)
Threshold limit algae 1	0.042 mg/l (72 h; Pseudokirchneriella subcapitata )

# 12.2. Persistence and degradability

No data available

# 12.3. Bioaccumulative potential

No data available

# 12.4. Mobility in soil

# No data available

## 12.5. Other adverse effects

PBT/vPvB assessment not available as chemical safety assessment not required/ not conducted An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

07/28/2015 AF33 6/10

# **SECTION 13: Disposal considerations**

13.1. Waste treatment methods

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No

discharge to surface waters is allowed without an NPDES permit.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be

released into the environment.

### **SECTION 14: Transport information**

In accordance with DOT

14.1. UN number

UN-No.(DOT) : 1263 DOT NA no. UN1263

14.2. UN proper shipping name

DOT Proper Shipping Name : PAINT

Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable liquid

Hazard labels (DOT) : 3 - Flammable liquid

3

Packing group (DOT) : III

14.3. Additional information

Transportation by land(ADG Code)

Transport document description : UN 1263 ,PAINT,3,III

Packaging group : III

Hazard Class 3- Flammable liquid

Hazchem Code : 3Y

Class labels : 3 - Flammable liquid



Transport by sea

UN-No. (IMDG) : 1263 Packaging Group III

Class (IMDG) : 3- Flammable liquid

EmS-No.(1): F-EEmS-No.(2): S-EMarine PollutantYes

Air transport

UN-No. (IATA) : 1263

Class (IATA) : 3- Flammable liquid

07/28/2015 AF33 7/10

# Safety Data Sheet

Packaging group (IATA) : III

DOT Quantity Limitations Passenger aircraft/rail (49 :

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

Other information : No supplementary information available.

## **SECTION 15: Regulatory information**

#### 15.1. US Federal regulations

All components of this product are listed on the United States TSCA (Toxic Substances Control Act) inventory.

Cumene (98-82-8)	
Listed on the United States TSCA (Toxic Substances C Listed on United States SARA Section 313	Control Act) inventory
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	5000 lb
SARA Section 313 - Emission Reporting	1 %
Benzene, 1,2,4-trimethyl- (95-63-6)	
Listed on the United States TSCA (Toxic Substances C Listed on United States SARA Section 313	Control Act) inventory
SARA Section 313 - Emission Reporting	1 %
Ethylbenzene (100-41-4)	
Listed on the United States TSCA (Toxic Substances C Listed on United States SARA Section 313	Control Act) inventory
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	1000 lb
SARA Section 313 - Emission Reporting	0.1 %
Toluene (108-88-3)	
Listed on the United States TSCA (Toxic Substances C Listed on United States SARA Section 313	Control Act) inventory
Benzene (71-43-2)	
Listed on the United States TSCA (Toxic Substances C Listed on United States SARA Section 313	Control Act) inventory
RQ (Reportable quantity, section 304 of EPA's List of Lists):	10 lb (recieved an adjusted RQ of 10 lbs based on potential carcinogenicity in an August 14, 1989 final rule)
SARA Section 313 - Emission Reporting	0.1 %
Arsenic (7440-38-2)	
Listed on the United States TSCA (Toxic Substances C Listed on United States SARA Section 313	Control Act) inventory
RQ (Reportable quantity, section 304 of EPA's List of Lists):	1 lb (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is $>100~\mu m)$
SARA Section 313 - Emission Reporting	0.1 %

# 15.2. International regulations

#### CANADA

No additional information available

# 15.2.2. National regulations

# Ethylbenzene (100-41-4)

Listed on IARC (International Agency for Research on Cancer)

Listed on Inventory of Existing Chemical Substances (IECSC)

Listed on the AICS (the Australian Inventory of Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.

Listed on the Korean ECL (Existing Chemical List) inventory.

# Cuprous oxide (1317-39-1)

Listed on the AICS (the Australian Inventory of Chemical Substances)

Listed on Inventory of Existing Chemical Substances (IECSC)

Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.

Listed on KECI (Chemical Inventory of Korea)

07/28/2015 **AF33** 8/10

# Safety Data Sheet

#### 15.3. US State regulations

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

Ethylbenzene (100-41-4)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
Cumene (98-82-8)		- 1	1	
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
Toluene (108-88-3)		- 1	1	
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	Yes	No	No	
Benzene (71-43-2)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	Yes	No	Yes	
Nickel (7440-02-0)		1	1	l
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
Lead (7439-92-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	Yes	Yes	Yes	
Silica: Crystalline, quartz (148	808-60-7)	- 1	1	
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
Arsenic (7440-38-2)		1	l	I
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
		1	1	

## Ethylbenzene (100-41-4)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

# Cumene (98-82-8)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

# Toluene (108-88-3)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

## Benzene (71-43-2)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Special Hazardous Substances
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

07/28/2015 **AF33** 9/10

# Safety Data Sheet

### Nickel (7440-02-0)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) Special Hazardous Substances

#### Lead (7439-92-1)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

#### Silica: Crystalline, quartz (14808-60-7)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Massachusetts Right To Know List

# Arsenic (7440-38-2)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Massachusetts Right To Know List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) Special Hazardous Substances

### Chlorinated paraffin waxes and hydrocarbon waxes (63449-39-8)

U.S. - Massachusetts - Right To Know List

#### Pseudocumene (95-63-6)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Massachusetts Right To Know List

### Cuprous oxide (1317-39-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

#### Zinc oxide (1314-13-2)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

# 15.4. Australian regulations

Poison Schedule (SUSMP): None allocated APVMA: 69531

AICS: All the constituents of this material are either listed on the Australian Inventory of Chemical Substance(AICS), not required due to

the nature of the chemical, or have been assessed under the national Industrial Chemicals ( Notification and Assessment)

Act 1989 as amended

#### **SECTION 16: Other information**

 $\begin{tabular}{ll} Indication of changes & : Revision 1.0 - 07/28/2015 - New SDS Created. \\ Other information & : Mario Garneau, edited by DeGroot Technical Services \\ \end{tabular}$ 

LITERARY REFERENCE: ADG Code - Australian Code for the Transportation of Dangerous Goods by Road and Rail (7th edition)

AICS - Australian Inventory of Chemical Substances

APVMA - Agricultural Pesticides and Veterinary Medicines Australia SUSMP - Standard for the Uniform Scheduling of Medicines & poisons

The information on this Data Sheet represents our current data and best opinion as to the proper use in handling of this material under normal conditions. Any use of the material which is not in conformance with this Data Sheet or which involves using this material in combination with any other material or any other process is the responsibility of the user. All materials present unknown health hazards and should be used with caution. Although certain hazards are described herein, the manufacturer and its agents cannot guarantee that these are the only hazards which exist. Further, the manufacturer and its agents assume no responsibility for personal injury or property damage to vendors, users, or third-parties caused by this material. User assumes all risks associated with the use of this material. No warranty, express or implied, is made and New Nautical Coatings, Inc assumes no liability resulting from the use of this SDS. The user must dtermine suitability of this information for his application.

07/28/2015 AF33 10/10