Safety Data Sheet

Date of issue: 07/28/2015

Revision date: 04/27/2017

Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking			
1.1. Product identifier			
Product name	: Cukote		
Product form	: liquid		
Other means of identification	: 3400 series		
1.2. Relevant identified uses of the substance or mixture and uses advised against			
Use of the substance/mixture	: Antifouling		
1.3. Details of the supplier of the safety data sheet			
Sea Hawk Paints Oceania NZ	New Nautical Coatings Inc. Mfg.		
21-23 Timothy Place Avondale	14805 49 <sup>th</sup> Street		
Auckland New Zealand 1026	Clearwater Florida USA 33762		
Phone +64210350506	USA Only: 1-800-528-0997 International: (727) 523-8053		
1.4. Emergency telephone numbers			
Emergency number : CHEMTREC day or night inside USA & Canada		A & Canada	
	1-800-424-9300		
	: CHEMTREC day or night outside USA & Canada		
	+1-703-741-5970		
	: Poison Control Center		
	USA 1-800-222-1222 AU +61 13 11 26 NZ 0800 764 766		

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## Classification (GHS-US)

Flam. Liq. 3	H226
Acute Tox. 4	H302
Asp. Tox. 1	H304
Aquatic Chronic 1	H410
Aquatic Acute 1	H400
Skin Sens. 1	H317
Carc. 1A	H350

Contains 9.5% ingredients of unknown oral toxicity.

### 2.2. Label elements

## **GHS-US** labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)	Danger
Hazard statements (GHS-US)	: H226 - Flammable liquid and vapor
	H304 – May be fatal if swallowed and enters airways
	<ul> <li>H302 - Harmful if swallowed</li> <li>H317 - May cause an allergic skin reaction</li> <li>H350 - May cause cancer</li> <li>H400 - Very toxic to aquatic life</li> <li>H410- Very toxic to aquatic life with long lasting effects</li> </ul>
Precautionary statements (GHS-US)	: P201 - Obtain special instructions before use
	P202 - Do not handle until all safety precautions have been read and understood
	P210 - Keep away from heat/sparks/open flames/hot surfaces No smoking
	P233 - Keep container tightly closed
	P240 - Ground/bond container and receiving equipment
	P241 - Use explosion-proof electrical/ventilating/lighting equipment

\_

P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P261 - Avoid breathing fumes or mist.
P264 - Wash face, hands and forearms thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P272 - Contaminated work clothing must not be allowed out of the workplace
P273 - Avoid release to the environment
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or a doctor.
P301+P312 - If swallowed: Call a doctor if you feel unwell
P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P308+P313 - If exposed or concerned: Get medical advice/attention
P321 - Specific treatment (see first aid instructions on this label)
P330 - Rinse mouth
P331 - Do NOT induce vomiting
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P370+P378 - In case of fire: Use water to extinguish
P391 - Collect spillage
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to licenced waste handling facility. NZEPA Approval: HSR000921
HSNO: 3.1C, 6.1D, (ALL), 6.3B, 6.4A, 6.5B, 6.7B, 6.8B, 6.8C, 6.9B (ALL) 9.1A, (ALL) 9.3B

#### 2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

## **SECTION 3: Composition/information on ingredients**

#### 3.1. Substance

Sdstance type:

: Multi-constituent		
Name	Product identifier	%
Cupric oxide	(CAS No) 1317-38-0	1-5
Solvent naphtha(petroleum), light aromatic	(CAS No) 64742-95-6	10-30
Ethylbenzene	(CAS No) 100-41-4	0.01 - 1
Zinc oxide	(CAS No) 1314-13-2	5-10
Cuprous oxide	(CAS No) 1317-39-1	35-50
Cumene	(CAS No) 98-82-8	0.1-1
Pseudocumene	(CAS No) 95-63-6	5-10
C18-28 Long Chain Chlorinated Paraffins	(CAS No) 63449-39-8	0.1-1
Reaction product of epichlorohydrin and bisphenol A	(CAS No) 25085-99-8	0.1-1
Crystalline silica (quartz)	(CAS No) 14808-60-7	0.1-1

Full text of H-phases: see section 16

3.2. Mixture

Not applicable

## **SECTION 4: First aid measures**

4.1. Description of first aid measures		
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medica label where possible).	l advice (show the
First-aid measures after inhalation	: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathin POISON CENTER or doctor/physician.	ng. Call a
First-aid measures after skin contact	: IF ON SKIN: Immediately rinse with plenty of water (for at least 15 minutes). Get imme advice/attention.	diate medical
First-aid measures after eye contact	: IF IN EYES: Rinse immediately and thoroughly, pulling the eyelids well away from the minimum). Get medical advice/attention.	eye (15 minutes
07/28/2015	Cukote	2/10

First-aid measures after ingestion	: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.	
4.2. Most important symptoms and effects, both acute and delayed		
Symptoms/injuries after inhalation : May cause nose and throat irritation.		
Symptoms/injuries after skin contact : May cause skin irritation. May cause allecgic skin reaction.		
Symptoms/injuries after eye contact : May cause eye irritation. Avoid contact with eyes.		
Symptoms/injuries after ingestion	: Harmful if swallowed. May cause abdominal pain, nausea, vomiting or drowsiness.	
Chronic symptoms	: Possible cancer hazard. Contains ingredients which may cause cancer based on animal data.	

## 4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.

SECTION 5: Firefighting measures			
5.1. Extinguishing media			
Suitable extinguishing media : Carbon dioxide. Dry powder.Alcohol-resistant foam.Water spray.			
5.2. Special hazards arising from the substance or mixture			
Fire hazard : Flammable liquid and vapor. May produce carbon oxides under fire conditions.			
Explosion hazard : Product is not explosive.			
Reactivity : No dangerous reactions known under normal conditions of use.			
5.3. Advice for firefighters			
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment.		
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear se contained breathing apparatus and protective suit (see item 8).			

SECT	TION 6: Accidental release me	sures	
6.1.	Personal precautions, protective e	ipment and emergency procedures	
Genera	I measures	: Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained clean-up crews proper equipped with respiratory equipment and full chemical protective gear (see Section 8).	erly
6.1.1.	For non-emergency personnel		
Protect	ve equipment	: Wear protective equipment as described in Section 8.	
Emerge	ency procedures	: Evacuate unnecessary personnel.	
6.1.2.	For emergency responders		
Protect	ive equipment	: Wear suitable protective clothing, gloves and eye or face protection. Wear approved supplied-air respirator, in case of emergency.	
6.2.	<b>Environmental precautions</b>		
Prevent	entry to sewers and public waters. Ave	release to the environment.	
6.3.	Methods and material for contain	ent and cleaning up	
For con	tainment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.	
Method	Is for cleaning up	: Exclude sources of ignition and ventilate the area. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Place in a suitable container for disposal in accordance with waste regulations (see Section 13). Waste from this product may be hazardous.	the
6.4.	Reference to other sections		
No add	itional information available		
SECT	<b>TION 7: Handling and storage</b>		
7.1.	Precautions for safe handling		
Precaut	ions for safe handling	Do not handle until all safety precautions have been read and understood. Wash hands and other exp areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide a ventilation in process area to prevent formation of vapor. Do not breathe mists. Keep away from sou ignition - No smoking. Use appropriate personal protection equipment (PPE).	good
7.2.	Conditions for safe storage, including any incompatibilities		
Storage	conditions	: Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container closed when not in use.	
Storage	temperature	: < 38 °C (100°F)	
7.3.	Specific end use(s)		
No add	itional information available		
07/28/20	015	Cukote	3/10

Safety Data Sheet

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

## Exposure

Ethylbenzene (100-41-4)			
ACGIH TWA (ppm)	20 ppm		
OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>		
OSHA PEL (TWA) (ppm)	100 ppm		
OSHA PEL (STEL) (mg/m <sup>3</sup> )	545 mg/m <sup>3</sup>		
OSHA PEL (STEL) (ppm)	125 ppm		
Zinc oxide (1314-13-2)			
ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>		
ACGIH STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>		
Cuprous oxide (1317-38-0)			
ACGIH TWA (ppm)	No Established Limit		
ACGIH STEL (ppm)	No Established Limit		
Cumene (98-82-8)			
ACGIH TWA (ppm)	50 ppm		
OSHA PEL (TWA) (mg/m <sup>3</sup> )	245 mg/m <sup>3</sup>		
OSHA PEL (TWA) (ppm)	50 ppm		
Silica: Crystalline, quartz (14808-60-7)			
ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable fraction)		
OSHA PEL (TWA) (mg/m <sup>3</sup> )	(10)/(%SiO2 + 2) total dust; (10)/(%SiO2 + 2) respirable fraction		
OSHA PEL (TWA) (ppm)	(250)/(%SiO2 + 5) respirable fraction		
Chlorinated paraffin waxes and hydrocarbon waxes (63449-39-8)			
Remark (ACGIH)	OELs not established		
Remark (OSHA)	OELs not established		

## 8.2. Exposure controls

Appropriate engineering controls Personal protective equipment

- : Ensure adequate ventilation, especially in confined areas.Handle with good industrial hygiene and safety.
- : Face shield. Respiratory protection of the dependent type. Gloves. Protective goggles. Protective clothing.



Hand protection	: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Natural rubber ("latex"), Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl.
Eye protection	: Eye protection, including both chemical splash goggles and face shield, must be worn when possibility exists for eye contact due to spraying liquid or airborne particles.
Skin and body protection	: Wear long sleeves.Handle with gloves
Respiratory protection	: An approved organic vapor respirator/supplied air or self-contained breathing apparatus must be used when vapor concentration exceeds applicable exposure limits.

## SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties		
Physical state	: Liquid	
Appearance	: liquid.	
Color	: Red, Blue and Black	
Odor	: Aromatic odour.	
Odor Threshold	: No data available	
pH	: No data available	
Relative evaporation rate (butyl acetate=1)	: Not Measured	
Relative evaporation rate (ether=1)	: Not Measured	
Melting point	: No data available	

## **Cukote** Safety Data Sheet

Freezing point	: No data available
Boiling point	: Not Measured
Flash point	: 38°C (101°F)-closed cup
Self ignition temperature	: Na data avilable
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: Not Measured
Relative vapor density at 20 °C	: Heavier than air
Relative density	: 2.2 g/ml at 25°C (77°F)
Solubility	: Water: None
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

## 9.2. Other information

No additional information available

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Upon combustion: CO and CO2 are formed. Reacts violently with strong oxidizers: increased risk of fire/explosion.reacts with some acids.

### 10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

### 10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air.

### 10.4. Conditions to avoid

Sparks. Heat. Open flame. Extremes of tempearture and direct sunlight.

### 10.5. Incompatible materials

Avoid contact with : Strong oxidizing agents.

## 10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

# SECTION 11: Toxicological information 11.1. Information on toxicological effects

Ethylbenzene (100-41-4)		
LD50 oral rat	3500 mg/kg	
LD50 dermal rabbit	15354 mg/kg	
LC50 inhalation rat (mg/l)	17.2 mg/l/4h	
ATE (oral)	3500.000 mg/kg body weight	
ATE (dermal)	15354.000 mg/kg body weight	
ATE (dust, mist)	1.500 mg/l/4h	
Cuprous oxide (1317-39-1)		
LD50 oral rat	470 mg/kg Category 4	
LD50 skin rabbit	2000.00 mg/kg Category 4	
LD50 inhalation vapor rat	No data available	
LD50 inhalation dust/mist rat	50.00 mg/l/4h Category NA	
7		
Zinc oxide (1314-13-2)		
LD50 oral rat	5000 mg/kg Category 5	
LD50 skin rabbit	No data available	
LD50 inhalation vapor rat	No data available	
07/28/2015	Cukote	

Safety Data Sheet

Zinc oxide (1314-13-2)	
LD50 inhalation dust/mist mouse	2.50 mg/l/4h Category 4
Cumene (98-82-8)	
LD50 oral rat	1400 mg/kg
LD50 dermal rabbit	12300 µg/kg
LC50 inhalation rat (ppm)	> 3577 ppm 6 h
Silica: Crystalline, quartz (14808-60-7)	
LD50 oral rat	500 mg/kg
Carcinogenicity data:	
Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
Cumene (98-82-8)	
IARC group	2B - Possibly carcinogenic to humans
Toluene (108-88-3)	
IARC group	3 - Not classifiable
Silica: Crystalline, quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
Arsenic (7440-38-2)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens
Chlorinated paraffin waxes and hydrocarbon waxe	s (63449-39-8)
IARC group	2B - Possibly carcinogenic to humans
Skin corrosion/irritation :	Not classified
Serious eye damage/irritation :	Not Applicable, Not classified
Respiratory or skin sensitization :	May cause an allergic skin reaction.
Germ cell mutagenicity :	Not Applicable, Not classified
Carcinogenicity :	May cause cancer
Acute Toxicity(Mouth)	Harmful if swallowed.
Acute Toxicity( skin)	Not Classified
Reproductive toxicity :	Not Applicable, Not classified
	Not Applicable, Not classified
specific target organ toxicity (single exposure)	
	Not Applicable, Not classified

## **SECTION 12: Ecological information**

12.1. Toxicity

Cuprous oxide (1317-39-1)		
LC50 fishes 1	0.075 mg/l (96 h;danio rerio)	
EC50 daphnia 1	0.042 mg/l (48 h; Daphnia similis)	
Threshold limit algae 1	0.03 mg/l (96 h; Pseudokirchneriella subcapitata)	
Zinc oxide (1314-13-2)		
LC50 fishes 1	1.10 mg/l (96 h; Oncorhynchus mykiss)	
EC50 daphnia 1	0.098 mg/l (48 h; Daphnia magna)	
Threshold limit algae 1	0.042 mg/l (72 h; Pseudokirchneriella subcapitata )	

## 12.2. Persistence and degradability

No data available

## 12.3. Bioaccumulative potential

No data available

## 12.4. Mobility in soil

No data available

## 12.5. Other adverse effects

PBT/vPvB assessment not available as chemical safety assessment not required/ not conducted An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
Waste treatment methods	. Do not discharge to public wastewater systems without permit of collution control systemiti-
waste u cathient methous	: Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.
Waste disposal recommendations	Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.
SECTION 14: Transport information	
In accordance with DOT	
14.1. UN number	
UN-No.(DOT)	: 1263
DOT NA no.	UN1263
14.2. UN proper shipping name	
DOT Proper Shipping Name	
DOT Proper Shipping Name	: PAINT
Department of Transportation (DOT) Hazard Classes	: 3 - Class 3 - Flammable liquid
Hazard labels (DOT)	: 3 - Flammable liquid
	3
Packing group (DOT)	: III
14.3. Additional information	
Transportation by land(ADG Code)	
Transport document description	: UN 1263 ,PAINT,3,III
Packaging group	
Hazard Class	3- Flammable liquid
Hazchem Code	: 3Y
Class labels	: 3 - Flammable liquid
	3
T (I	
Transport by sea	12/2
UN-No. (IMDG)	: 1263
Packaging Group	III
Class (IMDG)	: 3- Flammable liquid
EmS-No.(1)	: F-E
EmS-No.(2)	: S-E
Marine Pollutant	Yes
Air transnart	
<b>Air transport</b> UN-No. (IATA)	: 1263.
	: 1263. : 3- Flammable liquid

Packaging group (IATA) : III

DOT Quantity Limitations Passenger aircraft/rail (49 : CFR 173.27) DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)

Other information

: No supplementary information available.

## **SECTION 15: Regulatory information**

## 15.1. US Federal regulations

All components of this product are listed on the United States TSCA (Toxic Substances Control Act) inventory.

Cumene (98-82-8)		
Listed on the United States TSCA (Toxic Substances Listed on United States SARA Section 313	Control Act) inventory	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	5000 lb	
SARA Section 313 - Emission Reporting	1 %	
Benzene, 1,2,4-trimethyl- (95-63-6)		
Listed on the United States TSCA (Toxic Substances Listed on United States SARA Section 313	Control Act) inventory	
SARA Section 313 - Emission Reporting	1 %	
Ethylbenzene (100-41-4)		
Listed on the United States TSCA (Toxic Substances Listed on United States SARA Section 313	Control Act) inventory	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	1000 lb	
SARA Section 313 - Emission Reporting	0.1 %	
Toluene (108-88-3)		
Listed on the United States TSCA (Toxic Substances Listed on United States SARA Section 313	Control Act) inventory	
Benzene (71-43-2)		
Listed on the United States TSCA (Toxic Substances Listed on United States SARA Section 313	Control Act) inventory	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	10 lb (recieved an adjusted RQ of 10 lbs based on potential carcinogenicity in an August 14, 1989 final rule)	
SARA Section 313 - Emission Reporting	0.1 %	
Arsenic (7440-38-2)		
Listed on the United States TSCA (Toxic Substances Listed on United States SARA Section 313	Control Act) inventory	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	1 lb (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is $>100 \ \mu m$ )	
SARA Section 313 - Emission Reporting	0.1 %	

## 15.2. International regulations

## CANADA

No additional information available

### 15.2.2. National regulations

Ethylbenzene (100-41-4)	
Listed on IARC (International Agency for Research on Cancer)	
Listed on Inventory of Existing Chemical Substances (IECSC)	
Listed on the AICS (the Australian Inventory of Chemical Substances)	
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.	
Listed on the Korean ECL (Existing Chemical List) inventory.	
Cuprous oxide (1317-39-1)	
Listed on the AICS (the Australian Inventory of Chemical Substances)	
Listed on Inventory of Existing Chemical Substances (IECSC)	
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.	
Listed on KECI (Chemical Inventory of Korea)	

Listed on KECI (Chemical Inventory of Korea)

**15.3. US State regulations** This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

	ontain, trace quantities of a subs			
<b>Ethylbenzene (100-41-4)</b> U.S California - Proposition	U.S California -	U.S California - Proposition	U.S California - Proposition	No significance risk level
65 - Carcinogens List	Proposition 65 - Developmental Toxicity	65 - Reproductive Toxicity - Female	65 - Reproductive Toxicity - Male	(NSRL)
Yes	No	No	No	
Cumene (98-82-8)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
Toluene (108-88-3)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	Yes	No	No	
Benzene (71-43-2)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	Yes	No	Yes	
Nickel (7440-02-0)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
Lead (7439-92-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	Yes	Yes	Yes	
Silica: Crystalline, quartz (148	808-60-7)	-		·
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
Arsenic (7440-38-2)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	Yes	No	No	
Ethylbenzene (100-41-4)				
U.S New Jersey - Right to Kn U.S Massachusetts - Right To U.S Pennsylvania - RTK (Rig	Know List	azard List		
Cumene (98-82-8)				
U.S Massachusetts - Right To U.S New Jersey - Right to Kn U.S Pennsylvania - RTK (Rig	ow Hazardous Substance List	azard List		
Toluene (108-88-3)				
U.S Massachusetts - Right To U.S New Jersey - Right to Kn U.S Pennsylvania - RTK (Rig U.S Pennsylvania - RTK (Rig	ow Hazardous Substance List ht to Know) - Environmental Ha	azard List		
Benzene (71-43-2)				
U.S Massachusetts - Right To U.S New Jersey - Right to Kn U.S Pennsylvania - RTK (Rig U.S Pennsylvania - RTK (Rig	ow Hazardous Substance List ht to Know) - Special Hazardou			

Safety Data Sheet

ickel (7440-02-0)
S New Jersey - Right to Know Hazardous Substance List S Massachusetts - Right To Know List S Pennsylvania - RTK (Right to Know) - Environmental Hazard List S Pennsylvania - RTK (Right to Know) - Special Hazardous Substances
ead (7439-92-1)
.S New Jersey - Right to Know Hazardous Substance List .S Massachusetts - Right To Know List .S Pennsylvania - RTK (Right to Know) - Environmental Hazard List
ilica: Crystalline, quartz (14808-60-7)
.S New Jersey - Right to Know Hazardous Substance List .S Pennsylvania - RTK (Right to Know) List .S Massachusetts - Right To Know List
rsenic (7440-38-2)
<ul> <li>.S New Jersey - Right to Know Hazardous Substance List</li> <li>.S Massachusetts - Right To Know List</li> <li>.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List</li> <li>.S Pennsylvania - RTK (Right to Know) - Special Hazardous Substances</li> </ul>
hlorinated paraffin waxes and hydrocarbon waxes (63449-39-8)
.S Massachusetts - Right To Know List
seudocumene (95-63-6)
.S New Jersey - Right to Know Hazardous Substance List .S Pennsylvania - RTK (Right to Know) List .S Massachusetts - Right To Know List
uprous oxide (1317-39-1)
.S Massachusetts - Right To Know List .S New Jersey - Right to Know Hazardous Substance List .S Pennsylvania - RTK (Right to Know) - Environmental Hazard List
inc oxide (1314-13-2)
.S Massachusetts - Right To Know List .S New Jersey - Right to Know Hazardous Substance List .S Pennsylvania - RTK (Right to Know) - Environmental Hazard List

## 15.4. Australian regulations

 Poison Schedule (SUSMP):
 None allocated

 APVMA:
 69582

 AICS:
 All the constituents of this material are either listed on the Australian Inventory of Chemical Substance(AICS), not required due to the nature of the chemical, or have been assessed under the national Industrial Chemicals (Notification and Assessment)

 Act 1989 as amended.

<b>SECTION 16: Other information</b>	
Indication of changes	: Revision 1.0 – 07/28/ 2015 - New SDS Created.
Other information	: Mario Garneau, edited by DeGroot Technical Services

LITERARY REFERENCE: ADG Code - Australian Code for the Transportation of Dangerous Goods by Road and Rail (7th edition)

AICS – Australian Inventory of Chemical Substances

APVMA - Agricultural Pesticides and Veterinary Medicines Australia

SUSMP - Standard for the Uniform Scheduling of Medicines & poisons

The information on this Data Sheet represents our current data and best opinion as to the proper use in handling of this material under normal conditions. Any use of the material which is not in conformance with this Data Sheet or which involves using this material in combination with any other material or any other process is the responsibility of the user. All materials present unknown health hazards and should be used with caution. Although certain hazards are described herein, the manufacturer and its agents cannot guarantee that these are the only hazards which exist. Further, the manufacturer and its agents assume no responsibility for personal injury or property damage to vendors, users, or third-parties caused by this material. User assumes all risks associated with the use of this material.No warranty, express or implied, is made and New Nautical Coatings,Inc assumes no liability resulting from the use of this SDS. The user must dtermine suitability of this information for his application.