

**Sea
Hawk**
PREMIUM YACHT FINISHES



Outboard & Outdrive Underwater Primer

*For use with
Mission Bay Spray Paint*

500A

KEEP OUT OF REACH OF CHILDREN

DANGER

EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE, CONTENTS UNDER PRESSURE. See back/side panel for additional precautionary statements.

DISCLAIMER: The manufacturer warrants all material sold by it against defects in the material. The manufacturer's liability under the sale and warranty of this material shall in any case be limited to replacement of material only. The manufacturer makes no other warranty for this product, expressed or implied.

**Net Contents
12 fl.oz. (340 g)**

NEW NAUTICAL COATINGS, INC.
14805 49th Street North
Clearwater, FL 33762
727-523-8053
www.SeaHawkPaints.com

GENERAL DESCRIPTION: Outboard & Outdrive Primer 500A is formulated for use on underwater aluminum outdrives and outboards, prior to the application of Mission Bay Spray 4005A. Outboard & Outdrive Primer 500A is a non-bleeding anti-corrosive primer that provides an excellent barrier on underwater metal surfaces, reducing galvanic corrosion.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

APPLICATION: Shake can vigorously for at least 1 minute after mixing ball begins to rattle. Shake can often during use. Hold can 10-12 inches from surface and spray in short even passes to control film thickness and avoid runs. When finished spraying, invert can and spray until nozzle is clear.

Touch Dry	75°F (24°C)*	1 Hour Minimum
Dry To Overcoat	50°F (10°C)*	12 Hours Minimum
	75°F (24°C)*	8 Hours Minimum
	90°F (32°C)*	4 Hours Minimum

*Minimum Hull and Air Temperature

FOR ALUMINUM OUTBOARDS, OUTDRIVES, and HULLS

SURFACE PREPARATION: To prepare the surface for coating, remove all loose coatings and fouling residue by either washing with high pressure water, scraping or by disc sanding. Be sure to use the proper protective equipment to prevent inhalation or ingestion of the paint dust generated. Remove sanding dust with Sea Hawk 2033. Allow to dry and apply one coat of Outboard & Outdrive Underwater Primer 500A. Allow to dry per the above overcoating times and apply two coats of Mission Bay Spray 4005A in accordance to the can label. Unit may be put in service the following day.

NEW OUTDRIVES- FACTORY PAINTED: Lightly sand with 80-120 grit sandpaper, and wipe clean with Sea Hawk 2033. Allow to dry and apply one coat of Outboard & Outdrive Underwater Primer 500A. Allow to dry per the above overcoating times and apply first of two coats of Mission Bay Spray 4005A in accordance to the can label.

NEW or EXISTING UNITS – BARE METAL: Thoroughly sand to bright metal using 80-120 grit sandpaper and wipe clean with Sea Hawk 2033. Prime with one coat of S-75 Alumi-Chrome Primer followed by the first of two coats of Outboard & Outdrive Underwater Primer 500A. Allow to dry per above overcoating times. Then apply first of two coats of Mission Bay Spray 4005A in accordance to the can label.

CLEANUP: Use Sea Hawk 2033

COVERAGE: One can covers approximately 22 square feet. For application to hulls, apply 3 coats and allow proper dry times. Do NOT apply Outboard & Outdrive Primer 500A above the true waterline.

NJ/PA Right to Know Information

Color: Metallic Gold

CONTAINS: Acetone 67-64-1, Naphthas 64742-94-5 and 64742-95-6, Propane 74-98-6, Butane 106-97-8, Aluminum Flake 007429-90-5, and Aromatic Hydrocarbons 25154-85-2.

PRECAUTIONARY STATEMENTS

VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADEACHE, OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. DO NOT PUNCTURE OR INCINERATE (BURN) CONTAINER. EXPOSURE TO HEAT OR PROLONGED EXPOSURE TO THE SUN MAY CAUSE BURSTING. DO NOT EXPOSE TO HEAT OR STORE AT TEMPERATURE ABOVE 120°F.

NOTICE: Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Vapors may ignite explosively. Keep away from heat, sparks, and open flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

USE UNDER WELL VENTILATED CONDITIONS

Do not breathe vapors or spray mist. Ensure fresh air during application and drying. If you experience eye watering, headaches or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use. Avoid prolonged or repeated contact with eyes, skin and clothing. Wash thoroughly after handling.

First Aid: If swallowed, call physician or poison control center immediately. If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. If swallowed, **do not induce vomiting**, get medical attention immediately.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with state and federal regulations.

FOR CHEMICAL EMERGENCY, SPILL, LEAK, EXPOSURE OR ACCIDENT, CALL TOLL FREE DAY OR NIGHT – CHEMTREC 1-800-424-9300, MEDICAL ADVISORY NUMBER: CONTACT YOUR LOCAL POISON CONTROL CENTER OR CALL 800-854-6813. READ AND UNDERSTAND THE MANUFACTURER'S MATERIAL DATA SAFETY SHEET PRIOR TO USING.