



New Nautical Coatings, Inc.  
14805 49th Street North • Clearwater, FL 33762  
1-800-528-0997 U.S.A. only • (727) 523-8053 International  
www.SeaHawkPaints.com

CHEMTREC 24-HR EMERGENCY RESPONSE NUMBER  
800-424-9300 • OUTSIDE US 703-527-3887  
CHEMTREC should only be called in the event of chemical  
emergencies involving spill, leak, fire, exposure, or accident  
involving chemicals.

### 1. Product Identification

Product Name: Sea Hawk Premium Gelcoat ISO/NPG Series      Revision Date: **July 2011**  
Product Use: **Gel Coat**      Prepared by: **Chief Chemist**  
Appearance: Clear, various colors  
Cas Number: **Mixture**  
Synonyms: **None**

### 2. Ingredients

1. CAS# 000136-52-7  
Cobalt 2-Ethylhexanoate, 12% Cobalt  
PCT by Weight: .1470  
Exposure Limit:

ACGIH TLV/TWA: .05 MG/CU.M. AS COBALT METAL, DUST AND FUME  
OSHA PEL/TWA: .05 MG/CU.M. AS COBALT METAL, DUST AND FUME

2. CAS# 000080-62-6  
Methyl Methacrylate  
PCT by Weight: 5.0000      VAPOR PRESSURE: 29.000 MMHG @ 68°F  
Exposure Limit:

ACGIH TLV/TWA: 100 PPM (410 MG/CU.M.)  
OSHA PEL/TWA: 100 PPM (410 MG/CU.M.)  
LD50, ORAL: 7.9 G/KG (RAT)  
LD50, DERMAL: 35.5 G/KG (RABBIT)  
LC50, INHALATION: >12,500 PPM/0.5 HR (RAT)

3. CAS# 000100-42-5  
STYRENE MONOMER  
PCT BY WEIGHT: 31.8660      VAPOR PRESSURE: 4.500 MMHG @ 68°F  
EXPOSURE LIMIT:

ACGIH TLV/TWA: 20 PPM (85 MG/CU.M.)  
ACGIH TLV/STEL: 40 PPM (170 MG/CU.M.)  
OSHA PEL/TWA: 100 PPM (8 HR TWA)  
OSHA PEL/CEILING: ACCEPTABLE MAX. PEAK: 600 PPM (5 MIN IN ANY 3 HRS)  
OSHA PEL/STEL: ACCEPTABLE CONCENTRATION: 200 PPM (15 MIN TWA)  
LD 50, ORAL: 4.37 G/KG (RAT)  
LD 50, DERMAL: >5 G/KG (RABBIT)  
OTHER: LCLo: 5000 PPM/8h (RAT)  
OTHER: NIOSH TWA: 50 PPM (215 MG/M3)  
OTHER LIMITS: IARC-GROUP 2B SEE SECTION V

4. CAS# 013463-67-7  
TITANIUM DIOXIDE  
PCT BY WEIGHT: 14.0990  
EXPOSURE LIMIT:

ACGIH TLV/TWA: 10 MG/CU.M., (TOTAL DUST)  
OSHA PEL/TWA: 15 MG/CU.M., (TOTAL DUST)  
LD50, ORAL: >7500 MG/KG (RAT)  
LD50, DERMAL: NOT AVAILABLE  
LD50, INHALATION: NOT AVAILABLE



### 2. Ingredients (cont.)

5. CAS# 014807-96-6

Talc (Hydrous Magnesium Silicate)

PCT by Weight: 1-5

Exposure Limit:

ACGIH TLV/TWA:	2 MG/CU.M., RESPIRABLE DUST
OSHA PEL/TWA:	2 MG/CU.M., RESPIRABLE DUST
LD50, ORAL:	NOT AVAILABLE
LD50, DERMAL:	NOT AVAILABLE
LC50, INHALATION:	NOT AVAILABLE

6. CAS# 112945-52-5

Silica, Amorphous

EPA CASN: 7631-86-9

PCT by Weight: >1

Exposure Limit:

ACGIH TLV/TWA:	10 MG/M3
OSHA PEL/TWA:	15 MG/M3-TOTAL DUST; 5 MG/M3- TOTAL RESPIRABLE DUST

7.

Unsaturated Polyester Resin

ON TSCA INVENTORY/ON CANADIAN NDSL

CAS# PROPRIETARY

PCT BY WEIGHT: 30-40

EXPOSURE LIMIT:

ACGIH TLV/TWA:	NONE ESTABLISHED
OSHA PEL/TWA:	NONE ESTABLISHED

- This product contains one or more reported carcinogens or suspected carcinogens which are noted by NTP, IARC, or OSHA-Z in the appropriate subsection above under "other limits"
- This substance is classified as a hazardous air pollutant

### 3. Physical Data

Boiling Range:	High: N/A	Low: 212.0°F
Vapor Pressure:	See Section II	
Theoretical Weight per Gallon, Calculated:	10.5025 LB/GL	
Theoretical Specific Gravity, Calculated:	1.262	
Theoretical VOC, Calculated:	3.888 LB/GL	
(If applicable, see Section X for further VOC information)		
Physical State:	Liquid	
Appearance:	White	
Odor:	Moderate Aromatic	
Odor Threshold:	N/A	
pH:	N/A	
Freezing Point:	N/A	
Water Solubility:	Insoluble	
Coefficient of Water/Oil Distribution:	N/A	
Mechanical Impact Explosion:	No Known Hazard	
Static Electricity Explosion:	Avoid Static Charge	
% HAP by Weight:	37.008	
% Monomer by Weight	36.858	



#### 4. Fire and Explosion Hazard Data

**FLAMMABILITY CHARACTERISTICS:**

Lowest Closed Cup Flashpoint: 82.0°F

For Flash Points 73° to 100°F

OSHA Flammability classification: Class IC

DOT Flammability Classification: Flammable Liquid

Lower Flammable Limit in Air: Lower 1.1% by volume

DOT Shipping Name:

UN1866, Resin Solution, 3, PGIII

**EXTINGUISHING MEDIA:**

Foam, Carbon Dioxide, Dry Chemical, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:**

If polymerization takes place in a container, there is a possibility of violent rupture of the container. Vapors are uninhibited and may form polymers in vents or flame arrestors of storage tanks resulting in stoppage of vents. Vapors may cause flash fire. Keep containers tightly closed and isolate from heat, electrical equipment, sparks and flame. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

**SPECIAL FIRE FIGHTING PROCEDURES:**

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible auto-ignition or explosion when exposed to extreme heat.

**ADDITIONAL TRANSPORTATION INFORMATION:**

Freight Classification: NMFC: 46030 RESIN COMPOUNDS, LIQUID LTL CLASS 55

#### 5. Health Hazard Data

**EFFECTS OF EXCESSIVE OVEREXPOSURE. PRIMARY ROUTES OF ENTRY ARE:****EYE CONTACT:** Irritation. Symptoms are tearing, redness and discomfort.**SKIN CONTACT:** Can cause defatting of skin which may lead to dermatitis.**INHALATION:** Irritation to nose and throat. Extended or repeated exposure to concentrations above the recommended exposure limits may cause brain or nervous system depression, with symptoms such as dizziness, headache or nausea and if continued indefinitely, loss of consciousness, liver and kidney damage.**INGESTION:** May cause mouth, throat, esophagus and stomach irritation, nausea, vomiting and diarrhea.**MEDICAL CONDITIONS THAT MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT:** Preexisting eye, skin, liver, kidney and respiratory disorders.**EMERGENCY AND FIRST AID PROCEDURES:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If affected by inhalation of vapors or spray mist, remove to fresh air. If swallowed, get medical attention immediately. Based on the presence of components (03).**CALIFORNIA PROPOSITION 65 INFORMATION:****WARNING:** This product contains a chemical(s) known to the State of California to cause cancer.**OTHER HEALTH HAZARDS:****STYRENE MONOMER**

The International Agency for Research on Cancer (IARC) has reclassified styrene as Group 2B "possibly carcinogenic to humans". This new classification is not based on new health data relating to either humans or animals, but on a change in the IARC classification system. The Styrene Information and Research Center does not agree with the reclassification and has published the following statement. "Recently published studies tracing 50,000 workers exposed to high occupational levels of styrene over a period of 45 years showed no association between styrene and cancer, no increase in cancer among styrene workers (as opposed to the average among all workers), and no increase in mortality related to styrene."

An increased incidence of lung tumors was observed in mice from a recent inhalation study. The relevance of this finding is uncertain. Data from other long-term animal studies and from epidemiology studies of workers exposed to styrene do not provide a basis to conclude that styrene is carcinogenic. Lung effects have been observed in the mouse following repeated exposure to styrene.



## 5. Health Hazard Data (cont.)

**TALC:** Talc, Hydrous Magnesium Silicate, contains crystalline silica at levels greater than 0.1% but less than 1.0%. "IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, Supplement 7, 1987", concludes there is limited evidence for the carcinogenicity of crystalline silica to humans, Class 2A. This classification was based on exposure to free silica dust and is not expected to be relevant to trace amounts of crystalline silica dispersed in paints and plastics.

**METHYL METHACRYLATE:** Skin exposure to methyl methacrylate may cause irritation and/or rash; it is also a potential skin sensitizer. Prolonged or repeated overexposure at near lethal concentrations can cause liver and kidney damage.

## 6. Reactivity Data

**Stability:** Stable

**HAZARDOUS POLYMERIZATION:** May occur.

**CONDITIONS TO AVOID:** Elevated temperatures. improper addition of promoter and/or catalyst. Avoid direct contact of MEKP catalyst with accelerator. If an accelerator such as cobalt drier is to be added, mix this accelerator with base material before adding catalyst.

**INCOMPATIBILITY (MATERIALS TO AVOID):**

Oxidizers, reducing agents, peroxides, strong acids, bases, UV light, or any source of free radicals and mild steel.

**HAZARDOUS DECOMPOSITION PRODUCTS:**

Thermal decomposition or combustion can produce fumes containing organic acids, carbon dioxide and carbon monoxide.

## 7. Spill or Leak Procedures

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:**

Remove all sources of ignition (flames, hot surfaces, and electrical, static, or frictional sparks). Avoid breathing vapors. Ventilate area. Contain and remove with inert absorbent and non-sparking tools.

**WASTE DISPOSAL METHOD:**

Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers. Incinerate in approved facility.



## 8. Special Protection Information

### RESPIRATORY PROTECTION:

Do not breathe or ingest vapors, spray mist or dust while applying, sanding, grinding, or sawing cured product. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during application and other use of this product until vapors, mists and dusts are exhausted, unless air monitoring demonstrates vapor, mist and dust levels are below applicable limits. Follow respirator manufacturer's directions for respirator use. Observe OSHA Standard 29CFR 1910.134

### VENTILATION:

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the lower explosion limit and below current applicable exposure limits in the mixing, application and curing areas; and to remove decomposition product during welding and flame cutting on surfaces coated with this product. In confined areas, use only with forced ventilation adequate to keep vapor concentration below 20% of lower explosion limits. Refer to OSHA Standards 29CFR 1910.94, 1910.107, 1910.108

NOTE: Heavy solvent vapors should be removed from lower levels of the work area and all ignition sources (non explosion proof motors, etc.) should be eliminated

PROTECTIVE GLOVES: Use solvent impermeable gloves to avoid contact with product.

EYE PROTECTION: Do not get in eyes. Use safety eyewear with splash guards or side shields, chemical goggles, face shields.

OTHER PROTECTIVE EQUIPMENT: Avoid contact with skin. Use protective clothing. Prevent contact with contaminated clothing. Wash contaminated clothing, including shoes, before reuse.

## 9. Special Precautions

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Do not store above 100° F. Store large quantities in buildings designed to comply with OSHA 1910.106. Keep away from heat, sparks and flame. Keep containers closed when not in use and upright to prevent leakage.

### OTHER PRECAUTIONS:

Containers should be grounded when pouring. Do not take internally. Wash hands after using and before smoking or eating. Emptied containers may retain hazardous residue and explosive vapors. Keep away from heat, sparks and flames. Do not cut, puncture or weld on or near emptied containers. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed. If this product is blended with other components such as thinners, converter, colorants, and catalysts prior to use, read all warning labels. Any mixture of components will have hazards of all components. Follow all precautions. If spraying this material, keep spray booths clean. Avoid buildup of spray dust or overspray in booths or ducts.

### KEEP OUT OF REACH OF CHILDREN

### FOR INDUSTRIAL USE ONLY

### ADDITIONAL ENVIRONMENTAL INFORMATION:

The VOC quantity listed in Section III is a total theoretical loss value. Under typical conditions only half this amount might be lost to the atmosphere. Loss will vary due to temperature, humidity, film thickness, air movement, spray equipment/techniques, catalyzation, gel and cure rates, etc. If precise values are needed, it is suggested that onsite testing be conducted.

**10. Sara Title III Information**

## SARA 313 INFORMATION

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

COBALT 2-ETHYLHEXANOATE, 12% COBALT		
CAS# 000136-52-7	PCT by WT:	.1470
METHYL METHACRYLATE		
CAS# 000080-62-6	PCT by WT:	5.000
STYRENE MONOMER		
CAS# 0001000-42-5	PCT by WT:	31.8660

**New Nautical Coatings Inc.**

## Warranties, Disclaimers and Limitation of Liability

Seller warrants that: (i) Buyer shall obtain good title to the product sold hereunder; (ii) at shipment such product shall conform to Seller's specifications; and (iii) the sale of use of such product will not infringe the claims of any U.S. patent covering the product itself, but Seller does not warrant against infringement which might arise by the use of said product in any combination with other products or arising in the operation of any process. SELLER MAKES NO OTHER WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE, EVER IF THAT PURPOSE IS KNOWN TO SELLER. ANY APPLICATION INFORMATION OR ASSISTANCE WHICH SELLER MAY FURNISH TO BUYER IS GRATUITOUS AND SHALL IN NO WAY BE DEEMED PART OF THE SALE OF PRODUCT HEREUNDER OR A WARRANTY OF THE RESULTS OBTAINED THROUGH THE USE OF SUCH PRODUCT.

Without limiting the generality of the foregoing, if any product fails to meet warranties mentioned above, Seller shall at Seller's option either replace the nonconforming product at no cost to Buyer or refund Buyer the purchase price thereof. The foregoing is Buyer's sole and exclusive remedy for failure of Seller to deliver or supply product that meets the foregoing warranties. Seller's liability with respect to this contract and the product purchased under it shall not exceed the purchase price of the portion of such product as to which such liability arises. Seller shall not be liable for any injury, loss, or damage resulting from the handling or use of the product shipped hereunder whether in the manufacturing process or otherwise. In no event shall Seller be liable for special, incidental, or consequential damages including without limitations loss of profits, capital, or business opportunity, downtime costs, or claims of customers or employees of Buyer. Failure to give Seller notice of any claim within thirty (30) days of shipment of the product concerned shall constitute a waiver of such claim by Buyer. Any product credit received by Buyer hereunder, if not used, shall automatically expire one (1) year from the date the credit was granted. Notwithstanding any applicable statute of limitations to the contrary, any action by Buyer in relation to a claim hereunder must be instituted no later than two (2) years after the occurrence of the even upon which the claim is based. All the foregoing limitation shall apply irrespective of whether Buyer's claim is based upon breach of contract, breach of warranty, negligence, strict liability, or any other legal theory.