



FLEXIBLE PROTECTIVE COATING

- Use to Protect Fiberglass
- No Solvents
- Flexible UV Resistant Coating

Product Description

This acrylic strippable water-borne coating forms a tough, flexible, UV resistant temporary film that can be easily stripped after just a few hours, or stays flexible, pliable and strippable for months. Deck Protect contains no strong solvents that can mar or damage other surfaces. Deck Protect is intended for use as a protective coating over fiberglass gel coats or plastic laminates, but may be used to temporarily protect other surfaces providing suitability is conformed by test application. Deck Protect may be removed by manually peeling away coating or pressure washing.

Product Information

Item Number(s):	747
Color:	Translucent Blue
Finish/Sheen:	N/A
Resin:	Acrylic co-polymer
Converter:	One Pack
Volume Solids:	43%
Solids by Weight:	46.6%
Mix Ratio:	One Pack
Shipping Weight:	43-44 lbs./ 5 Gal.
Flash Point:	None
Film Thickness:	1 mil dry
Recommended Coats:	2
Theoretical Coverage:	50-80 Sq.Ft./Gal. @ recommended film thickness

Application Details

Method:	Brush, roller or spray
Induction/Sweat-in Time:	Not Applicable
Thinner:	None
Cleaner:	Soap & Water
Pot Life:	Not Applicable

Overcoating Interval

Substrate Temp.	Drying Time (Hrs)		
	Touch	Recoat	Full Cure
70°F (21°C)	.5-1 Hr	1-2 Hr	24 Hr

Do not apply when rain, cold or nightfall is imminent. Do not apply at temperature below 50°F. Drying and cure times are influenced by ambient temperature and relative humidity.

Consult your Sea Hawk Representative for the system best suited for surfaces to be protected.

NEW NAUTICAL COATINGS, INC.

14805 49th Street North • Clearwater, FL 33762 • 727.523.8053 • 800.528-0997 • FAX 727.523.7325

www.SeaHawkPaints.com

Limitations

Apply in good weather when air and surface temperatures are above 50°F (10°C). Surface temperature must be a least 50°F (10°C) above dew point. For optimum application properties, bring material to 70-80°F (21-27°C) temperature range prior to mixing and application. Unmixed material (in closed containers) should be maintained in protected storage between 40° and 100°F (4-38°C).

Technical and application data herein is for the purpose of establishing a general guideline of the coating and proper coating application procedures. As application, environmental and design factors can vary significantly due care should be exercised in the selection, verification of performance, and use of the coating.

Surface Preparation & Application

Remove all loose dirt and other surface contaminants before applying. Surface must be clean and dry.

Use brush, roller, or airless spray to apply. Apply unthinned. Apply generously to insure a thick uniform dry film. A thin, uneven film reduces effectiveness as a protective barrier and can tear making stripping difficult.

Cleanup & Removal

Clean up all areas with soap and water. Peel off or use water pressure to strip off dried film.

Application

Apply by brush, roller or spray. Apply 1 mil dry.

Brush: China Bristle
Roller: Solvent Resistant Roller Cover 3/8" pile smooth to medium Prewash Roller Cover to remove loose fibers prior to use.

Airless Spray: Minimum 30:1 ratio pump, min 1 gpm; 0.15-0-.026" orifice tip; 3/8" ID high-pressure material hose; 90 PSI line pressure; 60 mesh filter.

Thinning

NONE. This product may not be thinned.

Safety

Always wear safety goggles for eye protection. Wear protective gloves (butyl rubber or neoprene are recommended). Maintain adequate ventilation when working inside. When spraying use NIOSH approved chemical cartridge (organic vapor type) respiratory equipment, (a full-face respirator is recommended).

In case of inhalation - remove victim to fresh air and provide oxygen if breathing is difficult. In case of eye contact, flush with large quantities of water. In case of skin contact - wash skin with soap and water. Use emollient skin creams. In case of ingestion - do not induce vomiting. Call physician immediately.

Prior to use, obtain and consult the "Material Safety Data Sheet" of this product for health and safety information. Read and observe all precautionary notices on container labels.

NEW NAUTICAL COATINGS, INC.

14805 49th Street North • Clearwater, FL 33762 • 727.523.8053 • 800.528-0997 • FAX 727.523.7325

www.SeaHawkPaints.com