

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : 1277 BARRIER COAT
 Product form : Mixture
 Other means of identification : Chlorinated Rubber Based Primer

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

New Nautical Coatings, Inc.
 Sea Hawk Premium Yacht Finishes
 14805 49th Street North
 Clearwater, FL 33762
 USA Only: 1-800-528-0997
 International: (727) 523-8053

1.4. Emergency telephone numbers

Emergency number : CHEMTREC day or night inside USA & Canada
 1-800-424-9300
 : CHEMTREC day or night outside USA & Canada
 +1-703-741-5970
 : Poison Control Center
 1-800-222-1222

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 3	H226
Acute Tox. 4 (Inhalation:dust,mist)	H332
Skin Irrit. 2	H315
Skin Sens. 1	H317
Muta. 2	H341
Carc. 1B	H350
Repr. 2	H361

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapor
 H315 - Causes skin irritation
 H317 - May cause an allergic skin reaction
 H332 - Harmful if inhaled
 H341 - Suspected of causing genetic defects
 H350 - May cause cancer (Inhalation)
 H361 - Suspected of damaging fertility or the unborn child (Inhalation)

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
 P202 - Do not handle until all safety precautions have been read and understood
 P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
 P233 - Keep container tightly closed
 P240 - Ground/bond container and receiving equipment
 P241 - Use explosion-proof ventilating, electrical, lighting equipment
 P242 - Use only non-sparking tools
 P243 - Take precautionary measures against static discharge
 P261 - Avoid breathing vapors, spray
 P264 - Wash skin and clothing thoroughly after handling
 P271 - Use only outdoors or in a well-ventilated area
 P272 - Contaminated work clothing should not be allowed out of the workplace

1277 BARRIER COAT

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P280 - Wear eye protection, protective clothing, protective gloves, face protection
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P312 - Call a POISON CENTER/doctor/physician if you feel unwell
P321 - Specific treatment (see first aid instructions on this label)
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P362 - Take off contaminated clothing and wash before reuse
P370+P378 - In case of fire: Use carbon dioxide (CO₂), water, dry chemical powder, foam for extinction
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to licensed waste handling facility

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	30 - 60
m-Xylene	(CAS No) 108-38-3	15 - 40
Ethylbenzene	(CAS No) 100-41-4	7 - 13
o-Xylene	(CAS No) 95-47-6	7 - 13
p-Xylene	(CAS No) 106-42-3	5 - 10
Strontium chromate	(CAS No) 7789-06-2	3 - 7
Toluene	(CAS No) 108-88-3	0.1 - 1
Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, homopolymer	(CAS No) 25085-99-8	0.1 - 1

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.

First-aid measures after skin contact : IF ON SKIN: Immediately rinse with plenty of water (for at least 15 minutes). Get immediate medical advice/attention.

First-aid measures after eye contact : IF IN EYES: Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). Get medical advice/attention.

First-aid measures after ingestion : IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Harmful if inhaled. Causes skin irritation. May cause an allergic skin reaction. Suspected of causing genetic defects. Suspected of causing cancer (via inhalation). Suspected of damaging fertility or the unborn child.

Symptoms/injuries after inhalation : Harmful if inhaled. May affect the brain, nervous or respiratory system causing dizziness, headache, nausea or respiratory irritation. Overexposure can cause liver or kidney damage and CNS depression.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : May cause moderate irritation, including burning sensation, tearing, redness or swelling.

Symptoms/injuries after ingestion : Acute ingestion causes CNS depression, oropharyngeal and gastric pain and vomiting. May cause a light irritation of the linings of the mouth, throat, and gastrointestinal tract.

Chronic symptoms : Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. May cause cancer. May have mutagenic effect. May damage fertility. May damage the unborn child.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry powder. Foam.

1277 BARRIER COAT

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor.
Explosion hazard : Product is not explosive.
Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear self-contained breathing apparatus and protective suit (see item 8).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8).

6.1.1. For non-emergency personnel

Protective equipment : Wear Protective equipment as described in Section 8.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up : Exclude sources of ignition and ventilate the area. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Waste from this product may be hazardous as defined under RCRA (40 CFR 261).

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mists. Keep away from sources of ignition - No smoking. Use appropriate personal protection equipment (PPE).

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container closed when not in use.
Storage temperature : < 38 °C (100°F)

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Xylenes (o-, m-, p- isomers) (1330-20-7)	
ACGIH TWA (ppm)	100 ppm
ACGIH STEL (ppm)	150 ppm
OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA PEL (TWA) (ppm)	100 ppm
OSHA PEL (STEL) (mg/m ³)	655 mg/m ³
OSHA PEL (STEL) (ppm)	150 ppm

Toluene (108-88-3)	
ACGIH TWA (ppm)	20 ppm

1277 BARRIER COAT

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethylbenzene (100-41-4)	
ACGIH TWA (ppm)	20 ppm
OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA PEL (TWA) (ppm)	100 ppm
OSHA PEL (STEL) (mg/m ³)	545 mg/m ³
OSHA PEL (STEL) (ppm)	125 ppm

Oxirane, 2,2'-[1-methylethylidene]bis(4,1-phenyleneoxymethylene)]bis-, homopolymer (25085-99-8)	
Remark (ACGIH)	OELs not established
Remark (US OSHA)	OELs not established

m-Xylene (108-38-3)	
ACGIH TWA (ppm)	100 ppm
ACGIH STEL (ppm)	150 ppm
Remark (US OSHA)	OELs not established

Strontium chromate (7789-06-2)	
ACGIH TWA (mg/m ³)	0.0005 mg/m ³ (as Cr)
Remark (US OSHA)	OELs not established

p-Xylene (106-42-3)	
ACGIH TWA (ppm)	100 ppm
ACGIH STEL (ppm)	150 ppm
Remark (US OSHA)	OELs not established

o-Xylene (95-47-6)	
ACGIH TWA (ppm)	100 ppm
ACGIH STEL (ppm)	150 ppm
Remark (US OSHA)	OELs not established

8.2. Exposure controls

Appropriate engineering controls

: Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

: Face shield. Respiratory protection of the dependent type. Gloves. Protective goggles. Protective clothing.



Hand protection

: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Natural rubber ("latex"), Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl.

Eye protection

: Eye protection, including both chemical splash goggles and face shield, must be worn when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection

: Wear long sleeves.

Respiratory protection

: An approved organic vapor respirator/supplied air or self-contained breathing apparatus must be used when vapor concentration exceeds applicable exposure limits.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Yellow liquid.
Color	: No data available
Odor	: Solvent.
Odor Threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: < 1
Melting point	: No data available
Freezing point	: No data available

1277 BARRIER COAT

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Boiling point	: No data available
Flash point	: 27 °C (81°F)
Self ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: 2.4 mm Hg 77°C
Relative vapor density at 20 °C	: > 1 (Air = 1)
Relative density	: 1.24
Solubility	: Water: None
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: 1.1 - 6.6 vol %

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

An attempt to chlorinate xylene with 1,3-dichloro-5,5-dimethyl-2,4-imidazolidindione (dichlorohydrantoin) caused a violent explosion. The haloimide undergoes immediate self accelerating decomp in the presence of solvents.

10.4. Conditions to avoid

Sparks. Heat. Open flame.

10.5. Incompatible materials

Avoid contact with : Strong oxidizing agents. Strong acids.

10.6. Hazardous decomposition products

Thermal decomposition generates : Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if inhaled.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 oral rat	4300 mg/kg
LD50 dermal rabbit	> 1700 mg/kg
LC50 inhalation rat (mg/l)	47635 mg/l/4h
LC50 inhalation rat (ppm)	5000 ppm/4h
ATE (oral)	4300.000 mg/kg
ATE (dermal)	1100.000 mg/kg
ATE (dust, mist)	1.500 mg/l/4h

Toluene (108-88-3)	
LD50 oral rat	636 mg/kg
LD50 dermal rat	12124 mg/kg
LD50 dermal rabbit	8390 mg/kg
LC50 inhalation rat (mg/l)	12.5 mg/l/4h
LC50 inhalation rat (ppm)	> 26700 ppm/1h
ATE (oral)	636.000 mg/kg body weight
ATE (dermal)	8390.000 mg/kg body weight
ATE (dust, mist)	12.500 mg/l/4h

1277 BARRIER COAT

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15354 mg/kg
LC50 inhalation rat (mg/l)	17.2 mg/l/4h
ATE (oral)	3500.000 mg/kg body weight
ATE (dermal)	15354.000 mg/kg body weight
ATE (dust, mist)	1.500 mg/l/4h

m-Xylene (108-38-3)	
LD50 oral rat	5000 mg/kg (Source: IUCLID)
ATE (oral)	5000.000 mg/kg body weight
ATE (dermal)	1100.000 mg/kg body weight
ATE (dust, mist)	1.500 mg/l/4h

Strontium chromate (7789-06-2)	
ATE (oral)	500.000 mg/kg body weight

p-Xylene (106-42-3)	
LD50 oral rat	> 3392 mg/kg (Source: IUCLID)
LC50 inhalation rat (ppm)	4550 ppm/4h (Source: NLM_CIP)
ATE (dermal)	1100.000 mg/kg body weight
ATE (dust, mist)	1.500 mg/l/4h

o-Xylene (95-47-6)	
LD50 oral rat	3609 mg/kg (Source: IUCLID)
LC50 inhalation rat (ppm)	2180 ppm/4h (Source: IUCLID)
ATE (oral)	3609.000 mg/kg body weight
ATE (dermal)	1100.000 mg/kg body weight
ATE (dust, mist)	1.500 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Suspected of causing genetic defects.
Carcinogenicity : May cause cancer (Inhalation).

Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC group	3 - Not classifiable

Toluene (108-88-3)	
IARC group	3 - Not classifiable

Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Suspected of damaging fertility or the unborn child (Inhalation).
Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified
Aspiration hazard : Not classified
Symptoms/injuries after inhalation : Harmful if inhaled. May affect the brain, nervous or respiratory system causing dizziness, headache, nausea or respiratory irritation. Overexposure can cause liver or kidney damage and CNS depression.
Symptoms/injuries after skin contact : Causes skin irritation.
Symptoms/injuries after eye contact : May cause moderate irritation, including burning sensation, tearing, redness or swelling.
Symptoms/injuries after ingestion : Acute ingestion causes CNS depression, oropharyngeal and gastric pain and vomiting. May cause a light irritation of the linings of the mouth, throat, and gastrointestinal tract.
Chronic symptoms : Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. May cause cancer. May have mutagenic effect. May damage fertility. May damage the unborn child.

SECTION 12: Ecological information

12.1. Toxicity
No additional information available

1277 BARRIER COAT

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No.(DOT) : 1993
DOT NA no. : UN1993

14.2. UN proper shipping name

DOT Proper Shipping Name : Flammable liquids, n.o.s.
(Contains Xylene)

Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



DOT Symbols : G - Identifies PSN requiring a technical name
Packing group (DOT) : III - Minor Danger

14.3. Additional information

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Air transport

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L

SECTION 15: Regulatory information

15.1. US Federal regulations

1277 BARRIER COAT	
All chemical substances in this product are listed in the EPA (Environmental Protection Agency) TSCA (Toxic Substances Control Act) Inventory	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard

Xylenes (o-, m-, p- isomers) (1330-20-7)
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)

1277 BARRIER COAT

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Xylenes (o-, m-, p- isomers) (1330-20-7)	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	100 lb
SARA Section 313 - Emission Reporting	1 %

Toluene (108-88-3)
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)

Ethylbenzene (100-41-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)	
CERCLA RQ (Reportable quantity, section 304 of EPA's List of Lists) :	1000 lb
SARA Section 313 - Emission Reporting	0.1 %

Oxirane, 2,2'-(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, homopolymer (25085-99-8)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

m-Xylene (108-38-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)	
CERCLA RQ (Reportable quantity, section 304 of EPA's List of Lists) :	1000 lb
SARA Section 313 - Emission Reporting	1 % de minimis concentration

Strontium chromate (7789-06-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)	
CERCLA RQ (Reportable quantity, section 304 of EPA's List of Lists) :	10 lb

p-Xylene (106-42-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)	
CERCLA RQ (Reportable quantity, section 304 of EPA's List of Lists) :	100 lb
SARA Section 313 - Emission Reporting	1 % de minimis concentration

o-Xylene (95-47-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)	
CERCLA RQ (Reportable quantity, section 304 of EPA's List of Lists) :	1000 lb
SARA Section 313 - Emission Reporting	1 % de minimis concentration

15.2. International regulations

CANADA

Xylenes (o-, m-, p- isomers) (1330-20-7)
Listed on the Canadian DSL (Domestic Substances List) inventory.

Toluene (108-88-3)
Listed on the Canadian DSL (Domestic Substances List) inventory.

Ethylbenzene (100-41-4)
Listed on the Canadian DSL (Domestic Substances List) inventory.

Oxirane, 2,2'-(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, homopolymer (25085-99-8)
Listed on the Canadian DSL (Domestic Substances List) inventory.

m-Xylene (108-38-3)
Listed on the Canadian DSL (Domestic Substances List) inventory.

Strontium chromate (7789-06-2)
Listed on the Canadian DSL (Domestic Substances List) inventory.

p-Xylene (106-42-3)
Listed on the Canadian DSL (Domestic Substances List) inventory.

1277 BARRIER COAT

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

o-Xylene (95-47-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

No additional information available

15.2.2. National regulations

Xylenes (o-, m-, p- isomers) (1330-20-7)

Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on the Korean ECL (Existing Chemical List) inventory.

Toluene (108-88-3)

Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on the Korean ECL (Existing Chemical List) inventory.

Ethylbenzene (100-41-4)

Listed on IARC (International Agency for Research on Cancer)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on the Korean ECL (Existing Chemical List) inventory.

Oxirane, 2,2'-(1-methylethylidene)bis(4,1-phenyleneoxymethylene)jbis-, homopolymer (25085-99-8)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on KECI (Chemical Inventory of Korea)

m-Xylene (108-38-3)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on KECI (Chemical Inventory of Korea)

Strontium chromate (7789-06-2)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on KECI (Chemical Inventory of Korea)

p-Xylene (106-42-3)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on KECI (Chemical Inventory of Korea)

o-Xylene (95-47-6)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on KECI (Chemical Inventory of Korea)

15.3. US State regulations

Toluene (108-88-3)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	Yes	No	No	

Ethylbenzene (100-41-4)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

Xylenes (o-, m-, p- isomers) (1330-20-7)

1277 BARRIER COAT

Safety Data Sheet


Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Xylenes (o-, m-, p- isomers) (1330-20-7) U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Toluene (108-88-3) U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Ethylbenzene (100-41-4) U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
m-Xylene (108-38-3) U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - New Jersey - Right to Know Hazardous Substance List
Strontium chromate (7789-06-2) U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
p-Xylene (106-42-3) U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
o-Xylene (95-47-6) U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

SECTION 16: Other information

Indication of changes : Revision 1.0 – 29 Apr 2014 - New SDS Created.
Other information : Author. E.K.W.

NFPA health hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 3
Flammability : 2
Physical : 0
Personal Protection :

1277 BARRIER COAT

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information on this Data Sheet represents our current data and best opinion as to the proper use in handling of this material under normal conditions. Any use of the material which is not in conformance with this Data Sheet or which involves using this material in combination with any other material or any other process is the responsibility of the user. All materials present unknown health hazards and should be used with caution. Although certain hazards are described herein, the manufacturer and its agents cannot guarantee that these are the only hazards which exist. Further, the manufacturer and its agents assume no responsibility for personal injury or property damage to vendors, users, or third-parties caused by this material. User assumes all risks associated with the use of this material.