

THE INDUSTRY'S **BEST WRITTEN GUARANTEE**



Top Performing Triple-Biocide Antifouling



Colorkote[™]

- Triple Biocide Antifouling Power Econea*, Zinc Omadine, Copper Thiocyanate
- Vibrant Colors 6 Basic Colors can be mixed to create thousands of custom colors
- Multi-season performance in fresh, brackish and saltwater conditions
- California Air Quality Compliant 330 Grams
- ▶ Compatible with all hull types ideal for fiberglass, aluminum, and steel/iron hulls



Register

Certified



Bold Colors Block Barnacles

With Colorkote, 46,656 custom colors are possible by blending the 6 base colors above in various ratios.

4 White 1 Yellow

4 White 1 Red

1 Yellow 1 Red

1 Blue 1 Red

4 White 1 Green

1 Black

1 Yellow 1 White

1 White 1 Red

4 Red 1 Blue

4 Blue 1 Yellow

1 White 1 Green 1 White 1 Black

4 Yellow 1 White

4 Yellow 1 Red

4 Blue 1 Red 4 Yellow 1 Blue

4 Green 1 Yellow

1 Yellow 1 Blue

Top Performing Dual-Biocide Antifouling



Lloyd's

Register

Biocop TF™

- Advanced dual biocide PL3 technology
- Maximum protection available for fresh, brackish and saltwater
- Multi-season protection
- ▶ 38.06% Cuprous Oxide
- ▶ 4.14% Zinc Omadine
- Lloyd's Register certified



Black 1205-1

Light Blue 1202-1

Dark Blue 1230-1

Green 1234-1



Teal 1235-1

Gray 1231-1







Available in Black, Light Blue, Red and Gray



Gallons

Add a pint of Biocop TF to these Sea Hawk copper-based paints for DUAL-BIOCIDE Protection



= Biocop TF Slime Reducing Additive Compatible



BOTTOM PAINT BUYING GUIDE

Self-Polishing Copolymer Antifouling

Reducing

Cukote™

- Semi-hard, self-polishing ablative finish
- Multi-season protection
- ▶ 47.57% Cuprous Oxide
- Lloyd's Register certified

Register Certified







Blue 3442

330 VOC: 3442-L









Shark White 3410

Black 3445

330 VOC: 3445-L

AF33™

- Harder, self-polishing ablative finish
- Exceptional value multi-season coating
- ▶ 33.6% Cuprous Oxide highest grade available
- Consistent viscosity, better flow & rollability
- Lloyd's Register certified

















Dark Blue 3330



Red 3341



Green 3343



Semi-Hard Hybrid Ablative Antifouling

Talon™

- Value-priced
- 33.6% Cuprous Oxide
- Consistent viscosity, better flow & rollability

Slime Reducing Additive Compatible













ECONEA

Copper-Free Antifouling




Smart Solution™

- Metal-free self-polishing ablative antifoulant
- Environmentally safe
- Compatible over most existing antifoulants
- Econea
- Lloyd's Register certified Now Available in Pints for Outdrives











Dark Blue 4730

Bright Red 4701

Bright Green 4703

White 4710

Light Grey 4731 Available in quarts and pints

Water-Based Antifouling



Monterey™

- Water-based semi-hard ablative finish
- Environmentally safe low VOC's
- ▶ 54.67% Cuprous Oxide highest grade available







Blue 5442







Dark Blue 5430

OVER YEARS Hand Crafted in America . SM

Hard Modified Epoxy Antifouling



Tropikote[™]

- Hard, modified epoxy antifouling
- Protection in extreme tropical conditions
- > 75.8% Cuprous Oxide (Highest in the Industry)

Reducing Additive Compatible











Dark Blue 2140

Green 2143



Sharkskin[™]

- High performance hard modified epoxy
- ▶ 45.2% Cuprous Oxide
- Consistent viscosity better flow & rolling ability

Slime Reducing Additive Compatible













Dark Blue 6140

Red 6141

Green 6143

Download Technical and Safety Data Sheets at: www.SeaHawkPaints.com/sdss-tdss



Islands Dual-Biocide Antifouling

Islands 44 TF™

- Applies directly over tin-based paints
- Tin-free multi-season performance
- Highest grade of cuprous oxide available keeps barnacles away
- 32.7% Cuprous Oxide
- Econea biocide fights both hard and soft growth



Lloyd's











Dark Blue 1030TF

Red 1001TF

Teal 1035TF

Islands 77 Plus™ Dual-Biocide

- Highest Grade of Cuprous Oxide and Zinc Omadine Available
- Tin-Free Multi-Season Performance
- Consistent viscosity better flow & rollability
- Harder self-polishing polymer binding system















Red 7741

Green 7733

Gray 7731

Aluminum Boat Paint



Has no antifouling characteristics

Aluma Hawk™

- Ideal for pontoons, jon boats & house boats
- Rust-inhibiting
- Topcoat and/or primer on raw aluminum, fiberglass & other substrates
- Safe for fresh or saltwater submersion



Surface Tolerant Epoxy Coating



1241 Base and Catalysts sold separately

1241 Surface Tolerant Epoxy Coating System™

- Surface tolerant formulation, reduces surface preparation time and cost
- Low temperature cure expands application window (to 0°F, -18°C)
- Quick drying provides fast re-coating
- Low VOC formulation complies with rigid **VOC limits**
- Ideal for steel and aluminum hulls

Catalyst selection:

- 1241C Catalyst

Gray 1241

• 1241CS Slow Cure Catalyst



High Build Epoxy Primer Systems

Premium Blister Protection with Microsheet Silicate Technology

Tuff Stuff is an extremely high-build two-part epoxy primer that dries fast, enabling application of a complete barrier system and bottom paint in just two days. Using microsheet silicate technology, millions of microscopic sheets overlap and build a 100% water barrier that protects the surface from moisture and water penetration.



Available in 2-gal kit or 1/2-gal kit.

Tuff Stuff™

- ▶ Highest build epoxy primer
- ▶ Low odor during application
- ▶ All-in-one osmosis protection
- 1:1 two-part ratio for easy mixing



Gray 1284

White 1285



Available in 1-gal kit

Tuff Stuff™ Low VOC

- Highest build low VOC epoxy primer
- Complies with strict California Air Quality VOC limits
- ▶ Low VOC's (280 grams/liter)
- ▶ 1:1 two-part ratio for easy mixing



Gray 1286

White 1287

Primer Systems



1277 Bottom Paint Primer™

- ▶ Anti-corrosive bottom paint primer
- Ideal for priming any unknown antifoulant
- ▶ Indefinite overcoat window



SH-984 Shawkocon™

- Conversion/barrier/sealer coating over tin-based antifoulants and unknown well-adhered antifoulant
- Excellent barrier coat for underwater metals



S-76 Tack Coat Primer

S-76 Tack Coat Primer is for use on properly prepared steel, aluminum or galvanized steel. S-76 is an anti-corrosive primer that is specifically designed for underwater metal surfaces including hulls, running gear, and the lower units of outboards and I/O's. It provides an excellent barrier to reduce pitting of the metal from galvanic corrosion. S-76 should be used in conjunction with Tuff Stuff Epoxy Primer prior to applying antifoulant/topcoat.



Barnacle Blocker™ Spray Primer

- Self-cleaning anti-corrosive primer
- Use on underwater metals including steel, cast iron, copper, bronze, lead and aluminum
- Reduces galvanic corrosion
- Zinc-free aerosol spray

Gray 505A



TOUGH ON BARNACLES - QUALITY ASSURED!

www.SeaHawkPaints.com



OVER OVER YEARS Hand Crafted in America!

Epoxy Resin System

Hawk Epoxy





Hawk Epoxy Base Resin

Premium quality, marine-grade epoxy resin used for general fiberglass repair and construction with superior adhesion strength, bonding, filling and moisture barrier. Available in Quart (Size 1), Gallon (Size 2) & 5-Gallon (Size 3)



Hawk Epoxy Catalysts

C1 Ultra Slow Cure Catalyst - Very slow cure speed at room temperature. 3:1 ratio R1 Resin to C1.

Available in .66-Pint (Size 1), .33-Gallon (Size 2) & 1.45-Gallon (Size 3)

C2 Slow Cure Catalyst - Slow cure speed. Compatible with higher temperatures. 5:1 ratio R1 Resin to C2.

Available in .4-Pint (Size 1), .8-Quart (Size 2) & .87-Gallon (Size 3)

C3 Fast Cure Catalyst - Fast cure speed. Compatible with cooler temperatures. 5:1 ratio R1 Resin to C3.

Available in .4-Pint (Size 1), .8-Quart (Size 2) & .87-Gallon (Size 3)

C5 Clear Finish Catalyst - Cures to a very clear finish. Longer cure time in warmer temperatures. 3:1 ratio R1 Resin to C5.

Available in .66-Pint (Size 1), .33-Gallon (Size 2) & 1.45-Gallon (Size 3)



Hawk Epoxy Fillers

F1 High Load Adhesive Fiber Filler

F2 Structural Adhesive Filler

F3 Light Density Adhesive Micro Fiber Filler

F4 Bridging Adhesive Filler

F5 Light Density Fairing Filler

F6 MicroSphere Fairing Filler



Hawk Epoxy Pump Kits

Attaches directly to the resin and catalyst containers. Calibrated to yield the perfect mix ratio with one full pump stroke for both the resin and the catalyst.

Kit 30-KT for sizes 1 & 2. Kit 30-KT-S3 for size 3.



Klear Kote™ Table Top Resin

- Marine-grade, two-part epoxy system specifically for coating table tops, furniture and works of art that cures to a clear, glass-like surface
- Resists moisture, scratching and yellowing
- Exceptional self-leveling properties

Reducers & Solvents



2031 Islands 44 Reducer

2033 Reducer (General Purpose)

2035 Reducer (Above 85°)

2053 VOC-Exempt Reducer

2084 Tuff Stuff Reducer

7100 Mineral Spirits

7105 Denatured Alcohol

7110 Lacquer Thinner

7115 Toluene

7120 Acetone

7125 Methyl Ethyl Ketone

7135 VM&P Naptha

7130 Xylene

S-80 Wax 'N' Grease Killer

Specialty Products



1280 Marine Paint Stripper

- Removes most types of marine paint and
- Biodegradable, nonflammable, low odor, environmentally safe formula



S-90 Low VOC De-Waxing Etch & Cleaner

- Removes tough surface contaminates
- Water-based and biodegradable



Polyurethane Foam

- Provides excellent insulation, flotation and bonding
- Impervious to solvents and gasoline



Compatibility Chart Last modified: March 2021 **Previous** Fiberglass Bottomkote NT** Pacifica® Plus. **HRT Nepture*** Micron 66** Aquaguard **HRT Premium*** Odvssev HD* Protector* Agua One** Hydrocoat, SR, Eco* Ultima, SR, SSA, Eco* Trinidad (All)* Black Widow* Micron Navigator** Vivid* IIItra** **Fiberglass** Micron: WA, Extra, Trilux 33 Aerosol** **Bottomkote Aqua**** CSC, CSC HS, CF** MONTEREY **Unepoxy HRT*** HRT Eco* CUKOTE 330 MISSION BAY CSF SHARKSKIN ISLANDS 44 TF SMART SOLUTION TROPIKOTE AF 33 BIOCOP TF ISLANDS 77 PLUS TROPIKOTE BIOCIDE PLUS COLORKOTE ISLANDS 99 PLUS New CUKOTE MISSION BAY Top-Performing Triple Biocide COLORKOTE **Top-Performing Dual Biocide BIOCOP TF** ISLANDS 77 PLUS **ISLANDS 44 TF** Self-Polishing/Ablative CUKOTE **CUKOTE 330 VOC** AF 33 ISLANDS 99 PLUS **TALON** Hard Modified Epoxy TROPIKOTE SHARKSKIN Water-Based MONTEREY MISSION BAY CSF Copper-Free SMART SOLUTION **MISSION BAY** Products noted as such are registered Trademarks of, or sold by Pettit (KopCoat), and or RPM International, Inc. Compatibility Chart Legend:

Amount of Paint Needed per Coat

Boat Length (Feet)	Per Coat
20-25	3 Quarts
25-30	1 Gallon
30-32	1 Gallon + 1 Quart
33-37	1 Gallon + 2 Quarts
38-40	1 Gallon + 3 Quarts
41-42	2 Gallons
43-44	2 Gallons + 1 Quart
45-46	2 Gallons + 2 Quarts
47-49	2 Gallons + 3 Quarts
50-52	3 Gallons
53-55	3 Gallons + 1 Quart
56-59	3 Gallons + 2 Quarts

* Amounts are estimates and may vary by boat and bottom paint applied. Please see product technical data sheets for exact coverage.

Download Technical and Safety Data Sheets at: www.SeaHawkPaints.com/sdss-tdss

Lightly sand and apply paint

Heavily sand and apply paint

Follow us on Facebook Facebook.com/seahawkpaints

** Products noted as such are registered Trademarks of, or sold by Interlux, and or Akzo Nobel.



NEW NAUTICAL COATINGS, INC.

14805 49th Street North • Clearwater, Florida 33762 800.528.0997 U.S.A. Only • 727.523.8053 Int'l Email: ContactUs@SeaHawkPaints.com

www.SeaHawkPaints.com



AkzoNobel