

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Product name : Alumahawk  
Product form : Mixture  
Other means of identification : AH7033

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**1.3. Details of the supplier of the safety data sheet**

New Nautical Coatings, Inc.  
Sea Hawk Premium Yacht Finishes  
14805 49th Street North  
Clearwater, FL 33762  
USA Only: 1-800-528-0997  
International: (727) 523-8053

**1.4. Emergency telephone numbers**

Emergency number : CHEMTREC day or night inside USA & Canada  
1-800-424-9300  
: CHEMTREC day or night outside USA & Canada  
+1-703-741-5970  
: Poison Control Center  
1-800-222-1222

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**GHS-US classification**

Flam. Liq. 3 H226  
Acute Tox. 4 (Oral) H302  
Eye Irrit. 2A H319  
Skin Sens. 1 H317  
Muta. 1B H340  
Carc. 1A H350  
Repr. 2 H361  
STOT RE 2 H373  
Asp. Tox. 1 H304  
Aquatic Acute 2 H401  
Aquatic Chronic 2 H411

**2.2. Label elements**

**GHS-US labelling**

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

**Danger**

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapour  
H302 - Harmful if swallowed  
H304 - May be fatal if swallowed and enters airways  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H340 - May cause genetic defects  
H350 - May cause cancer  
H361 - Suspected of damaging fertility or the unborn child  
H373 - May cause damage to organs through prolonged or repeated exposure  
H401 - Toxic to aquatic life  
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking

# Alumahawk

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof ventilating equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P260 - Do not breathe dust, fume, gas, mist, spray, vapours  
P261 - Avoid breathing dust, fume, gas, mist, spray, vapours  
P264 - Wash hands, forearms and face thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P272 - Contaminated work clothing must not be allowed out of the workplace  
P273 - Avoid release to the environment  
P280 - Wear eye protection, protective gloves, protective clothing  
P301+P310 - IF SWALLOWED: Immediately call a doctor, a poison center  
P301+P312 - If swallowed: Call a doctor, a poison center if you feel unwell  
P302+P352 - If on skin: Wash with plenty of soap and water  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308+P313 - If exposed or concerned: Get medical advice/attention  
P314 - Get medical advice/attention if you feel unwell  
P321 - Specific treatment (see first aid instructions on this label)  
P330 - Rinse mouth  
P331 - Do NOT induce vomiting  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P370+P378 - In case of fire: Use alcohol resistant foam, sand, carbon dioxide (CO<sub>2</sub>) to extinguish  
P391 - Collect spillage  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste

### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

### 2.4. Unknown acute toxicity (GHS US)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%
Methyl isobutyl ketone	(CAS No) 108-10-1	7 - 13
Methyl propyl ketone	(CAS No) 107-87-9	3 - 7
Solvent naphtha, petroleum, light aliphatic	(CAS No) 64742-89-8	3 - 7
Toluene	(CAS No) 108-88-3	1 - 5
1-Butanol	(CAS No) 71-36-3	1 - 5
Trizinc diphosphate	(CAS No) 7779-90-0	1 - 5
Isobutyl isobutyrate	(CAS No) 97-85-8	0.5 - 1.5
Ethylbenzene	(CAS No) 100-41-4	0.1 - 1
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	0.1 - 1
Oxirane, methyl-, polymer with oxirane, monobutyl ether	(CAS No) 9038-95-3	0.1 - 1
Silica: Crystalline, quartz	(CAS No) 14808-60-7	0.1 - 1
Cobalt neodecanoate	(CAS No) 27253-31-2	0.1 - 1
Naphthenic acids, cobalt salts	(CAS No) 61789-51-3	0.1 - 1
Naphtha, petroleum, hydrotreated heavy	(CAS No) 64742-48-9	0.1 - 1
Zirconium ethyl hexoate	(CAS No) 22464-99-9	0.1 - 1
Methyl ethyl ketoxime	(CAS No) 96-29-7	0.1 - 1
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]-	(CAS No) 104810-47-1	0.1 - 1
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy-	(CAS No) 104810-48-2	0.1 - 1

# Alumahawk

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.
- First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. Get medical attention immediately.
- First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Get medical attention immediately. Continue rinsing.
- First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Harmful if swallowed. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. Causes serious eye irritation. May cause genetic defects. May cause cancer. Suspected of damaging fertility. Suspected of damaging the unborn child. Causes damage to organs (central nervous system). May cause damage to organs through prolonged or repeated exposure.
- Symptoms/injuries after inhalation : May cause respiratory irritation.
- Symptoms/injuries after skin contact : May cause an allergic skin reaction.
- Symptoms/injuries after eye contact : Causes serious eye irritation.
- Symptoms/injuries after ingestion : Harmful if swallowed. May be fatal if swallowed and enters airways.
- Chronic symptoms : May cause genetic defects. May cause cancer. Suspected of damaging fertility. Suspected of damaging the unborn child. Causes damage to organs. May cause damage to organs through prolonged or repeated exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry powder. Alcohol-resistant foam. Sand.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapour.
- Explosion hazard : Product is not explosive. Under fire conditions closed containers may rupture or explode.
- Reactivity : No dangerous reactions known under normal conditions of use.

#### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Protective equipment : Wear Protective equipment as described in Section 8.
- Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Scoop solid spill into closing containers or bags. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Exclude sources of ignition and ventilate the area. Waste from this product may be hazardous as defined under RCRA (40 CFR 261).

# Alumahawk

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.4. Reference to other sections

No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact with eyes. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Containers of this material may be hazardous when emptied. Do not breathe mist, spray.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep only in the original container in a cool, well ventilated place away from : Direct sunlight, Heat sources. Keep container closed when not in use.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

<b>Methyl propyl ketone (107-87-9)</b>	
ACGIH STEL (ppm)	150 ppm
OSHA PEL (TWA) (mg/m <sup>3</sup> )	700 mg/m <sup>3</sup>
OSHA PEL (TWA) (ppm)	200 ppm
OSHA PEL (STEL) (mg/m <sup>3</sup> )	875 mg/m <sup>3</sup> Vacated
OSHA PEL (STEL) (ppm)	250 ppm Vacated
<b>Toluene (108-88-3)</b>	
ACGIH TWA (ppm)	20 ppm
Remark (ACGIH)	Visual impair; female repro;
<b>Ethylbenzene (100-41-4)</b>	
ACGIH TWA (ppm)	20 ppm
Remark (ACGIH)	upper respiratory tract irritation; kidney damage (nephropathy); cochlear impairment
OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA PEL (TWA) (ppm)	100 ppm
OSHA PEL (STEL) (mg/m <sup>3</sup> )	545 mg/m <sup>3</sup>
OSHA PEL (STEL) (ppm)	125 ppm
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
ACGIH TWA (ppm)	100 ppm
ACGIH STEL (ppm)	150 ppm
OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA PEL (TWA) (ppm)	100 ppm
OSHA PEL (STEL) (mg/m <sup>3</sup> )	655 mg/m <sup>3</sup>
OSHA PEL (STEL) (ppm)	150 ppm
<b>Oxirane, methyl-, polymer with oxirane, monobutyl ether (9038-95-3)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Silica: Crystalline, quartz (14808-60-7)</b>	
ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable fraction)
OSHA PEL (TWA) (mg/m <sup>3</sup> )	(30)/(%SiO <sub>2</sub> + 2) total dust; (10)/(%SiO <sub>2</sub> + 2) respirable fraction
OSHA PEL (TWA) (ppm)	(250)/(%SiO <sub>2</sub> + 5) respirable fraction
<b>Methyl isobutyl ketone (108-10-1)</b>	
ACGIH TWA (ppm)	20 ppm
ACGIH STEL (ppm)	75 ppm
OSHA PEL (TWA) (mg/m <sup>3</sup> )	410 mg/m <sup>3</sup>

# Alumahawk

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Methyl isobutyl ketone (108-10-1)</b>	
OSHA PEL (TWA) (ppm)	100 ppm
<b>Cobalt neodecanoate (27253-31-2)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Naphthenic acids, cobalt salts (61789-51-3)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Naphtha, petroleum, hydrotreated heavy (64742-48-9)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Zirconium ethyl hexoate (22464-99-9)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Methyl ethyl ketoxime (96-29-7)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Trizinc diphosphate (7779-90-0)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>1-Butanol (71-36-3)</b>	
ACGIH TWA (ppm)	20 ppm
OSHA PEL (TWA) (mg/m <sup>3</sup> )	300 mg/m <sup>3</sup>
OSHA PEL (TWA) (ppm)	100 ppm
<b>Solvent naphtha, petroleum, light aliphatic (64742-89-8)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Isobutyl isobutyrate (97-85-8)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]- (104810-47-1)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established
<b>Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy- (104810-48-2)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established

### 8.2. Exposure controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

: Gloves. Protective goggles. Protective clothing. Insufficient ventilation: wear respiratory protection.



Hand protection

: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.

# Alumahawk

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye protection	: Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.
Skin and body protection	: Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.
Respiratory protection	: Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment with gas filter (type A2). Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Green.
Odor	: No data available
Odor Threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 16 °C (60.8 °F)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 1.38
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

#### 10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

#### 10.3. Possibility of hazardous reactions

None known.

#### 10.4. Conditions to avoid

Sparks. Heat. Open flame. Extremely high or low temperatures. Direct sunlight.

#### 10.5. Incompatible materials

No data available.

#### 10.6. Hazardous decomposition products

No data available.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed.

# Alumahawk

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Methyl propyl ketone (107-87-9)</b>	
LD50 oral rat	1600 mg/kg
LD50 dermal rat	6480 mg/kg
LC50 inhalation rat (ppm)	2000 ppm/4h
<b>Toluene (108-88-3)</b>	
LD50 oral rat	2600 mg/kg
LD50 dermal rabbit	12000 mg/kg
LC50 inhalation rat (mg/l)	12.5 mg/l/4h
<b>Ethylbenzene (100-41-4)</b>	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15400 mg/kg
LC50 inhalation rat (mg/l)	17.2 mg/l/4h
ATE CLP (gases)	4500.000 ppmv/4h
ATE CLP (vapours)	11.000 mg/l/4h
ATE CLP (dust,mist)	1.500 mg/l/4h
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
LD50 oral rat	3500 mg/kg
ATE CLP (dermal)	1100.000 mg/kg bodyweight
ATE CLP (gases)	4500.000 ppmv/4h
ATE CLP (vapours)	11.000 mg/l/4h
ATE CLP (dust,mist)	1.500 mg/l/4h
<b>Oxirane, methyl-, polymer with oxirane, monobutyl ether (9038-95-3)</b>	
LD50 oral rat	7460 mg/kg
LD50 dermal rabbit	14100 µl/kg
LC50 inhalation rat (mg/l)	0.147 mg/l/4h
<b>Silica: Crystalline, quartz (14808-60-7)</b>	
LD50 oral rat	500 mg/kg
<b>Methyl isobutyl ketone (108-10-1)</b>	
LD50 oral rat	2080 mg/kg
LD50 dermal rabbit	3000 mg/kg
ATE CLP (gases)	4500.000 ppmv/4h
ATE CLP (vapours)	11.000 mg/l/4h
ATE CLP (dust,mist)	1.500 mg/l/4h
<b>Trizinc diphosphate (7779-90-0)</b>	
LD50 oral rat	> 5000 mg/kg
<b>Naphtha, petroleum, hydrotreated heavy (64742-48-9)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
<b>Methyl ethyl ketoxime (96-29-7)</b>	
LD50 oral rat	930 mg/kg
LD50 dermal rabbit	0.2 mg/kg
LC50 inhalation rat (mg/l)	20 mg/l/4h
<b>1-Butanol (71-36-3)</b>	
LD50 oral rat	700 mg/kg
LD50 dermal rabbit	3402 mg/kg
LC50 inhalation rat (ppm)	> 8000 ppm/4h
ATE CLP (oral)	500.000 mg/kg bodyweight
<b>Solvent naphtha, petroleum, light aliphatic (64742-89-8)</b>	
LD50 oral rat	5000 mg/kg mouse
LD50 dermal rabbit	3000 mg/kg
<b>Isobutyl isobutyrate (97-85-8)</b>	
LC50 inhalation rat (ppm)	5000 ppm 6 h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: May cause genetic defects.

# Alumahawk

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carcinogenicity : May cause cancer.

<b>Toluene (108-88-3)</b>	
IARC group	3 - Not classifiable
<b>Ethylbenzene (100-41-4)</b>	
IARC group	2B - Possibly carcinogenic to humans
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
IARC group	3 - Not classifiable
<b>Silica: Crystalline, quartz (14808-60-7)</b>	
IARC group	1 - Carcinogenic to humans
<b>Methyl isobutyl ketone (108-10-1)</b>	
IARC group	2B - Possibly carcinogenic to humans
<b>Naphthenic acids, cobalt salts (61789-51-3)</b>	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Specific target organ toxicity (single exposure) : Causes damage to organs (central nervous system)

Specific target organ toxicity (repeated exposure) : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.

Symptoms/injuries after inhalation : May cause respiratory irritation.

Symptoms/injuries after skin contact : May cause an allergic skin reaction.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : Harmful if swallowed. May be fatal if swallowed and enters airways.

Chronic symptoms : May cause genetic defects. May cause cancer. Suspected of damaging fertility. Suspected of damaging the unborn child. Causes damage to organs. May cause damage to organs through prolonged or repeated exposure.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

### SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1263 Paint related material (including paint thinning, drying, removing, or reducing compound), 3, II

UN-No.(DOT) : 1263

DOT NA no. : UN1263

Proper Shipping Name (DOT) : Paint related material  
including paint thinning, drying, removing, or reducing compound

Department of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

# Alumahawk

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Minor Danger

DOT Quantity Limitations Passenger aircraft/rail : 60 L  
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L  
CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

### Additional information

Other information : No supplementary information available.

### Transport by sea

No additional information available

### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### Alumahawk

All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory

<b>1-Butanol</b>	<b>CAS #:</b> 71-36-3
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Section 302 (EHS) TPQ	lb
Section 304 EHS RQ	lb
CERCLA RQ	5000 lb
Section 313	Listed on US SARA Section 313

<b>Toluene</b>	<b>CAS #:</b> 108-88-3
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Section 302 (EHS) TPQ	lb
Section 304 EHS RQ	lb
CERCLA RQ	1000 lb
Section 313	Listed on US SARA Section 313

<b>Methyl isobutyl ketone</b>	<b>CAS #:</b> 108-10-1
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Section 302 (EHS) TPQ	lb
Section 304 EHS RQ	lb
CERCLA RQ	5000 lb
Section 313	Listed on US SARA Section 313

### 15.2. International regulations

#### CANADA

No additional information available.

### 15.3. US State regulations

#### California Proposition 65

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

# Alumahawk

## Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Toluene (108-88-3)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	Yes	No	No	
<b>Ethylbenzene (100-41-4)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
<b>Silica: Crystalline, quartz (14808-60-7)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	
<b>Methyl isobutyl ketone (108-10-1)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	Yes	No	No	
<b>Benzene (71-43-2)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	Yes	No	Yes	
<b>Methyl propyl ketone (107-87-9)</b>				
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Toluene (108-88-3)</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Ethylbenzene (100-41-4)</b>				
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List				
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List				
<b>Silica: Crystalline, quartz (14808-60-7)</b>				
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List				
<b>Methyl isobutyl ketone (108-10-1)</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List				
<b>Naphthenic acids, cobalt salts (61789-51-3)</b>				
U.S. - New Jersey - Right to Know Hazardous Substance List				
<b>1-Butanol (71-36-3)</b>				
U.S. - Massachusetts - Right To Know List				

# Alumahawk

## Safety Data Sheet


Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>1-Butanol (71-36-3)</b> U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
<b>Isobutyl isobutyrate (97-85-8)</b> U.S. - New Jersey - Right to Know Hazardous Substance List
<b>Benzene (71-43-2)</b> U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
<b>Barium sulfate (7727-43-7)</b> U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List
<b>Talc (14807-96-6)</b> U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

### SECTION 16: Other information

Indication of changes : Revision 4.0: Updated.  
Revision date : 05/14/2026  
Other information : Author: NMR.

NFPA health hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.  
NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all ambient conditions.  
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



**HMIS III Rating**  
Health : 3\*  
Flammability : 3  
Physical : 0  
Personal Protection :

The information on this Data Sheet represents our current data and best opinion as to the proper use in handling of this material under normal conditions. Any use of the material which is not in conformance with this Data Sheet or which involves using this material in combination with any other material or any other process is the responsibility of the user. All materials present unknown health hazards and should be used with caution. Although certain hazards are described herein, the manufacturer and its agents cannot guarantee that these are the only hazards which exist. Further, the manufacturer and its agents assume no responsibility for personal injury or property damage to vendors, users, or third-parties caused by this material. User assumes all risks associated with the use of this material.