

Clean Surface Preparation

- Designed for new fiberglass hulls to remove mold-release wax
- Removes tough surface contaminants
- Promotes primer and paint adhesion on most substrates



Concentrated Cleaning Formula



PRODUCT DESCRIPTION

S-80 consists of a concentrated petroleum-based formula which effectively removes tough surface contaminants. With its penetrating action, it is effective on wax, oil residues, surface soiling contaminants, and mold spores. Can also be used for cleaning boat hulls that have been stripped of old coatings in preparation for new primer and paint application.



PRODUCT INFORMATION

Shipping Weight: 7-8 Lbs/Gal

Flash Point: 27.2°C - 81°F

VOC: 6.94 Lbs/Gal / 832 Grams/Liter

BENEFITS VS. COMPETITION

- Deep cleaning for new hulls removed from hull molds
- Effectively removes microbial spore structures
- Quickly cuts through the toughest contaminants, such as grease and oil, for easier surface cleaning
- Concentrated strength formula
- Penetrates through contaminants effectively lifting them from the substrate
- Fast evaporation
- Low residue
- Lifts tough contaminants with minimal labor

DIRECTIONS FOR USE

General Cleaning

Apply S-80 generously with contaminate-free towel or cloth and rub gently to remove surface contaminants. Proper Personal Protective Equipment (PPE) should be worn all times when using S-80.

Always wash surfaces with soap and water, rinse and dry thoroughly before using S-80 to clean surfaces. After using S-80, wash the surface again with soap and water and let dry thoroughly.

Whenever possible wipe dry in one direction to reduce the possibility of smearing contaminants as they are removed.

Use in a well ventilated environment.

Revision date: May 5, 2026